



SUPER LIFE® 8000P **BENEFICIENT SYNTHETIC BLEND MOTOR OILS**

SUPER LIFE® 8000P Products are formulated with a mixture of high-tech synthetic and premium quality base stocks and the advanced additive technology to exceed the performance requirements of the current ILSAC GF-6 and API SP specifications and provide low-speed pre-ignition (LSPI) and timing chain wear protection while improving piston cleanliness, oxidation stability and fuel economy for the latest turbocharged gasoline direct injection (TGDI) engines. They are manufactured to help combat low-speed pre-ignition (LSPI) in turbocharged gasoline direct injection engines - the LSPI events that can cause premature wear, destroy pistons & connecting rods and catastrophic engine failure -

SUPER LIFE® 8000P Products provide extraordinary engine protection under all severe driving conditions, including heavy load and stop- and -go conditions, rapid acceleration, sudden stops and high revving all push the engine to work harder, run hotter and high and low-temperature engine operation.

APPLICATIONS:

SUPER LIFE® 8000P Products are recommended for turbocharged or naturally aspirated gasoline direct-injection, conventional gasoline-fueled, flex-fuel engines including gasoline-electric hybrid engines used in passenger cars, light-trucks vans operating in any type of severe service (extreme hot or cold climates, stop- and- go driving conditions, etc.).

SUPER LIFE® 8000P Products meet the requirements of major North America, Japanese and European OEMs: Mercedes Benz, BMW, Volkswagen, Fiat, Ford, General Motors, Chrysler, Toyota, Lexus, Honda, Acura, Nissan, Infinity, Subaru, Mazda, Hyundai, Kia, etc.

| SAE Viscosity Grade | 5W-20 | 5W-30 | 10W-30 | 10W-40 | 15W-40 | 20W-50 |
|------------------------|-------|-------|--------|--------|--------|--------|
| API SP, SN Plus, SN/SM | x | x | x | x | x | x |
| ILSAC GF-6A | x | x | x | | | |
| Resource Conserving | x | x | x | | | |
| Ford WSS-M2C945-B1 | x | | | | | |
| Ford WSS-M2C946-B1 | | x | | | | |
| Ford WSS-M2C960-A1 | x | | | | | |
| Ford WSS-M2C961-A1 | | x | | | | |
| Ford WSS-M2C962-A1 | x | | | | | |
| Chrysler MS-6395 | x | x | x | | | |
| GM 6094M | x | x | x | x | x | x |
| MB 229.3 | | x | | | | |
| BMW LL-O/M54 | x | x | x | x | x | x |
| VW 505.00 | | x | x | x | x | x |
| VW 505.01 | | x | x | x | x | x |
| CID AA-52039 | x | x | x | x | x | x |
| MIL-L-2104-B | x | x | x | x | x | x |
| MIL-L-46152 | x | x | x | x | x | x |

BENEFITS:

- Help protect against low speed pre-ignition (LSPI) in turbocharged gasoline direct-injection engines (TGDI)
- Maintain protective and thermal breakdown resistant oil films for engine parts.
- Protect against start up wear, rust, corrosion, and harmful deposits (sludge, varnish).
- Synthetic base for added oxidation stability, improved volatility and low temperature properties.

- Excellent resistance to viscosity and thermal breakdown at high temperatures.
- Flow easily at low temperatures for easy cold starting and rapid warm up.
- Low-friction formula improve gas mileage, fuel economy and maintain low emissions.
- Preserve engine cleanliness and extend engine life.

TYPICAL CHARACTERISTICS

| Test | Method | Test Results | | | | | |
|---------------------------------------|------------|---------------|----------------|----------------|-----------------|-----------------|-----------------|
| SAE Viscosity grade | SAE J300 | 5W-20 | 5W-30 | 10W-30 | 10W-40 | 15W-40 | 20W-50 |
| API Gravity | ASTM D287 | 34.97 | 33.42 | 32.48 | 32.65 | 32.08 | 31.14 |
| Specific gravity @ 15.6 °C (60°F) | ASTM D1298 | 0.850 | 0.858 | 0.861 | 0.862 | 0.865 | 0.870 |
| Viscosity @ 40°C, cSt @ 100°C, cSt | ASTM D445 | 50.45 8.80 | 67.20 11.30 | 66.40 10.40 | 105.80 15.80 | 101.40 14.22 | 164.15 19.50 |
| Viscosity Index | ASTM D2270 | 155 | 163 | 145 | 160 | 143 | 137 |
| Flash Point, °C (°F) | ASTM D92 | 203 (397) | 205 (401) | 205 (401) | 210 (410) | 212 (414) | 220 (428) |
| Pour Point, °C (°F) | ASTM D97 | -46 (-51) | -47 (-53) | -42 (-44) | -40 (-40) | -45 (-49) | -33 (-27) |
| HTHS Viscosity @150°C, cP | ASTM D4683 | 3.25 | 3.77 | 4.01 | 4.10 | 4.33 | 4.80 |
| Noack, %wt | ASTM D5800 | 10.90 | 10.80 | 7.10 | 7.00 | 8.40 | 4.95 |

The above characteristics are average values based on recent production. Minor variations, which do not affect product performance, are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference MSDS No: 12023 database on our website at www.amtecol.com

