



Specifications: Locktite Asbestos Encapsulant,
Available in Blue, Clear or White! 5 gallon Pail, 55 gallon Drum

Appearance: Milky / Opaque Liquid

Odor: Odorless

Boiling Point: Not determined

Evaporation Rate: < 1

pH: 8-11

Flash Point: Not flammable

DOT Shipping Class: 55

Shipping Weight: 5 gal. pail 45lbs.
55 gal. drum 510lbs

Specific Gravity: 1.0

Solubility: Complete in Water

Reactivity: Stable

HMS Rating: 1-0-0

Shelf Life: 2 years

DOT Shipping Name: NOT DOT REGULATED
MATERIAL

Twin-Chemicals
Atlanta, Georgia

(800) 442-4958
(770) 924-6147 fax

www.twinchemicals.com



PRONTO LOCKTITE is an economical and efficient asbestos lockdown encapsulant. This is a ready to use product that is designed to lock down asbestos fibers in your work areas and help you pass even the most aggressive air tests. **PRONTO LOCKTITE** penetrates asbestos rapidly and completely. When it penetrates, it absorbs onto the individual fibers to lock them together, reducing the possibility of loose fibers from becoming airborne during the removal process.

Directions:

1. Read and understand safety data sheet (SDS) when using this product.
2. Use full strength. Using an appropriate airless sprayer, mist all surfaces to lock down loose asbestos fibers on all fireproof insulation, protective barriers and ground/floor areas after any removal procedure.