



DESCRIPTION:

- Finely ground polymer material to be added to paint or stains to achieve a slip resistant surface
- For use on walkways, driveways, garage floors, patios, pool decks and other surfaces.
- It may also be added to paints to create a fine texture effect.

ORDERING:

- Available in 0.2 lb. and 1.0 lb. bottles.

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
9102 TALON GRIP SLIP RESISTANT ADDITIVE	910202	0.2 lb.	760428091027	7" x 7" x 9"	9 large & 12 small bottles per case	180 Cases
9105 TALON GRIP SLIP RESISTANT ADDITIVE	910510	1.0 lb	760428091058	13" x 10" x 9"		60 Units

PROPERTIES

Color(s)	White Powder Transparent in Clear Coatings
Gloss	Semi /Low Luster
Resin	Micronized Polypropylene
Recommended Addition	.18 lbs. (9102) to a 1G can .88 lbs. (9105) to a 5 G pail
Mean Particle Size	160-180 (microns) 50 (mesh)
Solvent Resistance	Can be used in most film forming water-based, solvent-based alkyds, paints, sealers, urethanes and epoxy coatings.

DIRECTIONS FOR USE AND SURFACE PREPARATION:

- For best results add entire contents to one gallon of Anvil Concrete Floor Sealer or Anvil Water Reducible Floor Stain and stir well.
- Stir periodically during application.

PRECAUTIONS

- **Caution:** Should be treated as a nuisance dust while incorporating it into it intended vehicle. Use with adequate ventilation. Use appropriate, properly fitted respiratory protection filter apparatus and avoid breathing dust and particles. If dizziness, headache or eye watering occurs, get to fresh air, leave the area. In case of eye contact, flush with large amounts of water. Get medical attention if irritation persists. Do not take internally. If swallowed get medical attention immediately.
- **Keep out of reach of children.**