



DESCRIPTION:

- Designed as a single product, non-aggregated, two-coat texture wall surfacing system that provides an ultra-tough, durable, breathable decorative commercial textured wall finish on interior walls and ceilings.
- 100% acrylic emulsion breakthrough product that produces a finish that is ideal for use in motels, hotels, offices, apartments, restaurants, health care and other high-traffic or commercial buildings.
- Remains slightly flexible when cured thereby making it extremely resistant to cracking and chipping under the most demanding commercial/hospitality environment.
- The coating can be used to create a level 5 drywall surface or a "splatter," "knockdown," or "orange peel" finish depending on the equipment and application technique used.
- Used on interior surfaces of drywall or masonry construction.

ORDERING:

- Available in 5 gallon buckets only.
- Coverage:
 - **As a level 5 finish**, 200 sq. ft./gallon
 - **As the texture coat**, 125 sq. ft./gallon (depending on the texture pattern desired, method of application and equipment used).
 - **Average coverage** is 100 -140 sq. ft./gal. (16.0 - 11.0 wet mils).

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
2020 TEXWALL MULTIPURPOSE TEXTURE SYSTEM	202005	5G	760428202058	12" x 12" x 15"	1	36 Cases

STORAGE & HANDLING:

- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID: In case of skin contact**, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. **For eye contact**, flush immediately with large amounts of water, for at least 15 minutes. **If swallowed**, get medical attention immediately. **If inhalation causes physical discomfort**, move to fresh air. **If discomfort persists** or any breathing difficulty occurs, get medical help.

PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.**
- **Warning! Irritant!** Harmful if swallowed, when tinted, contains ethylene glycol which can cause severe kidney damage when ingested and has been shown to cause birth defects in laboratory animals.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.



WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

2020 TEXWALL MULTI-PURPOSE TEXTURE SYSTEM

PROPERTIES	
Weight per Gallon	14.92 lbs.
Color(s)	Tint Base for most colors. Up to 8 oz. universal colorant per gallon
VOC Content	38.5 Grams per Liter (cal.)
Viscosity	140 KU @ 75° F
Solid Content by Weight	73 +/- 2%
Solid Content by Volume	54 +/- 2%
Resin	100% Acrylic modified for superior durability
Flash Point	None
Permeance	32.7 +/- 2% (ASTM D-1653)
Mildew Growth	(ASTM D3273) 0%
Fire & Smoke	(ASTM E84) non-combustible Class A
Scrub	(ASTM D-3363) 5000+ cycles no erosion
Pencil Hardness	2H (ASTM D-3363)
Total System DFT	10-12 mils
Dry Time @ 70°F & 50% RH Drying times are influenced by ambient temperature and relative humidity.	To Touch: 1 Hour To Recoat: 2 to 3 Hours Full Cure: 24 Hours

- Airless pump capacity and material hose size must be sufficient to support the tip selected.
- Apply the second texture coat at 11.0 - 16.0 wet mils which requires 100 - 140 sq. ft./gallon by hopper gun or through a texture pump and gun at package consistency (do not thin).
- Obtain “knock down” effect by smoothing the peaks with a stainless-steel trowel.
- Obtain an “orange peel” by spraying a light even pattern using high pressure and a small orifice.
- Drying time for “knock down effect” will vary due to temperature, humidity and other conditions, and is best determined by test applications.
- Texture coat can be troweled down with a stainless-steel trowel. Always work to a wet edge.
- Varying orifice size, air pressure and knock down technique will influence finish appearance.
- Experimentation and test application are recommended.
- Once a procedure has been determined to achieve the desired results all changes including applicator should be avoided until a different wall or natural breaking point has been reached.
- Can be tinted at store level with most color systems in pastel to medium shades.
- Use 1 gallon color formula (20%) as a starting point in color matching. Up to 8 oz. of colorant per gallon.

DIRECTIONS FOR USE AND SURFACE PREPARATION:

- Surface must be clean, dry, sound and paint ready.
- Wall surfaces should be dry, free of dust, grime or other contaminants that could interfere with the bonding characteristics of TEX WALL #2020.
- New masonry must be allowed to cure for at least 30 days.
- Remove all wallcoverings and excessive amounts of wallpaper adhesive residue. Strip any existing coatings which are loose and poorly bonded.
- Remove mildew and mold with a solution that kills mildew.

APPLICATION:

- A two-coat spray-designed system.
- To a level 4 drywall surface apply the base color coat by airless sprayer, using a .027 - .0231 tip.
- Apply at 8 - 10 mils wet, which requires an application rate of 160 - 200 sq. ft./gallon.
- It can be thinned with no more than 1 quart of water per 5 gallons to ease application, mix using a slow speed joint compound paddle.

COVERAGE DETAILS:

- **Level 5 Finish Base/Color Coat**, 160 - 200 sq. ft./gal. (10.0 - 8.0 wet mils).
- **Texture Coat**, 125 sq. ft./gal., coverage will vary according to surface porosity, texture pattern desired and equipment used.
- **Average coverage** is 100 -140 sq. ft./gal. (16.0 - 11.0 wet mils).
- A test application is recommended to determine actual coverage under specific job conditions.

MILDEW CONTROL:

- Allows moisture to escape and has mold and mildew growth inhibitors.
- Controlling moisture is the key to controlling mildew. Without moisture, mold and mildew cannot absorb nutrients and grow, no matter how many spores are present.
- Traditional vinyl wallcoverings contribute to moisture by acting as a vapor barrier.

CLEANUP: Water.