



DESCRIPTION:

- Specially formulated with Premium Pure Acrylic Resins for durability and ease of application over a wide range of properly prepared substrates.
- Excellent choice for residential re-paints, architectural and commercial applications demanding durability.
- Low odor, water reducible and non-flammable.
- Provides a flat finish with excellent high hiding properties, achieved by brush, roller or airless spray application.
- Formulated for interior and exterior applications where the professional painting contractor needs durability and ease of application with excellent wet and dry hiding power.

ORDERING:

- Available in 1 gallon cans and 5 gallon buckets.
- Coverage Rate: 200 to 400 sq. ft. per gallon, per coat depending on the type of surface and porosity

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
SEE PRODUCT DETAILS ON PAGE 3						

STORAGE & HANDLING:

- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID: In case of skin contact**, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. **For eye contact**, flush immediately with large amounts of water, for at least 15 minutes. **If swallowed**, get medical attention immediately. **If inhalation causes physical discomfort**, move to fresh air. **If discomfort persists** or any breathing difficulty occurs, get medical help.

PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.**
- **Warning! Irritant!** Harmful if swallowed, when tinted, contains ethylene glycol which can cause severe kidney damage when ingested and has been shown to cause birth defects in laboratory animals.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.



WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov



WARNING: This product can expose you to chemicals including Diuron, which is known to the State of California to cause birth defects and reproductive harm. For more information go to www.P65Warnings.ca.gov

7000 SERIES ANVIL SUPER PRO

PROPERTIES	
Weight per Gallon	10.25 lbs.
Color(s)	Tintable
Gloss	Semi-Gloss
VOC Content (cal.)	7001 - Semi-Gloss Pastel Tint Base 151.6 7002 - Semi-Gloss Medium Tint Base 153.2 7003 - Semi-Gloss Deep Tint Base 150.8 7004 - Semi-Gloss Accent Tint Base 147.8
Viscosity	95-100 KU @ 75° F
Solid Content by Weight	45%
Solid Content by Volume	32%
Resin	Acrylic
Flash Point	None
Dry Time @ 70°F & 50% RH Drying times are influenced by ambient temperature and relative humidity. Curing and drying time will affect the performance of the product. Allow a minimum of 30 days before cleaning.	To Touch: 1/2 Hour - 1 Hour To Recoat: 1 to 2 Hours

PREVIOUSLY PAINTED MASONRY

- Prime with Anvil 230 or 231 Chalky Surface Conditioner or Anvil 1606 Rust Inhibitive Universal Primer, self-prime if the surfaces are in good condition.

NEW WOOD, PLYWOOD, FERROUS METAL, GALVANIZED, RUSTED OR ALUMINUM

- Prime with Anvil 1606 Rust Inhibitive Universal Primer, if previously painted and in good condition self-prime.

APPLICATION:

- Do not apply when air, surface or product temperatures are below 50° F or above 100° F. Surface temperature must be at least 5° F above the dew point.
- Avoid spraying when damp or threatening weather is expected. Product must cure at least 8 hours before being subjected to moisture.
- Do not apply late in the day where dew or condensation may form before product begins to cure.
- During extremely hot weather, maintaining a wet edge may become difficult. Avoid application during the heat of the day.
- Mix thoroughly and stir frequently while using to maintain consistency.
- Ensure color uniformity, by inter-mixing product before use.
- Apply by brush, roller or airless sprayer. Work material vigorously into pores. Maintain a wet edge.
- If roller application is employed on porous surfaces, final passes should be completed in a downward direction to ensure a uniform appearance and texture.
- Apply at such a rate as to avoid runs and sags. If airless spray is employed, tip size should reflect equipment type and pressure, applicator technique and surface conditions. Generally a tip size between 0.015" and 0.021" is used.
- Adjust pressure for constant and proper atomization. Work to maintain a wet edge and on porous surfaces, immediate "back rolling" with wet roller is recommended to help reduce pin holing and to assist working the material into the pores.

DIRECTIONS FOR USE AND SURFACE PREPARATION:

- Surfaces must be completely dry and in sound condition.
- Surface should be clean and free from construction dust and dirt, grease, mill oils, rust, scale, chalky paint, efflorescence, organic growth, mildew or other foreign matter that would impair adhesion.
- Pressure washing, sandblasting, power tool cleaning, hand tool cleaning, scraping or wire brushing should be employed to remove peeling, chipping and cracking paint.
- All glossy surfaces should be sanded or de-glossed.
- Feather sand rough edges of previously painted surface and spot prime bare areas.
- All unpainted substrates should be properly prepared and primed with the recommended primers.

SUBSTRATES

FOR NEW GYPSUM WALLBOARD AND INTERIOR PLASTER,

- Allow all drywall joint compound and plaster thoroughly dry and prime with Anvil 235 AquaSeal or self-prime.

PREVIOUSLY PAINTED WALLBOARD OR PLASTER

- Prime with Anvil 235 AquaSeal or self-prime if the surfaces are in good condition.

NEW CONCRETE AND MASONRY,

- Prime alkaline substrate (pH range 8-10) with Anvil 1606 Rust Inhibitive Universal Primer or Anvil 345 "Hot" Block Filler.

CLEANUP:

- Clean all tools and equipment with warm soapy water immediately after use.
- Flush spray equipment thoroughly with clean water

7000 SERIES SUPER PRO

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
7001 SUPER PRO S GLOSS PTB 1G	70011	1G	760428700110	14" x 14" x 8"	4	54 Cases
7001 SUPER PRO S GLOSS PTB 5G	70015	5G	760428700158	12" x 12" x 15"	1	36 Cases
7001 SUPER PRO S GLOSS PTB 1Q	70014	1Q	760428700141	13" x 9" x 6"	6	90 Cases
7002 SUPER PRO S GLOSS ITB 1G	70021	1G	760428700219	14" x 14" x 8"	4	54 Cases
7002 SUPER PRO S GLOSS ITB 5G	70025	5G	760428700257	12" x 12" x 15"	1	36 Cases
7002 SUPER PRO S GLOSS ITB 1Q	70024	1Q	760428700240	13" x 9" x 6"	6	90 Cases
7003 SUPER PRO S GLOSS DTB 1G	70031	1G	760428700315	14" x 14" x 8"	4	54 Cases
7003 SUPER PRO S GLOSS DTB 5G	70035	5G	760428700352	12" x 12" x 15"	1	36 Cases
7003 SUPER PRO S GLOSS DTB 1Q	70034	1Q	760428700349	13" x 9" x 6"	6	90 Cases
7004 SUPER PRO S GLOSS ATB 1G	70041	1G	760428700417	14" x 14" x 8"	4	54 Cases
7004 SUPER PRO S GLOSS ATB 5G	70045	5G	760428700455	12" x 12" x 15"	1	36 Cases
7004 SUPER PRO S GLOSS ATB 1Q	70044	1Q	760428700448	13" x 9" x 6"	6	90 Cases