



DESCRIPTION:

- A water based, non-yellowing clear coating for glazing and sealing bare and colored brick and concrete pavers.
- Delivers a medium gloss when applied to a properly prepared surface and is highly resistant to the effects of hot car tires.
- It is formulated for use on exterior unsealed concrete pavers and concrete surfaces such as patios, walkways, decks and sidewalks.
- Formulated to be resistant to mild automotive chemicals, oil, grease and gasoline. Its durable acrylic formula also resists fading, scuffing, cracking, peeling and blistering.

ORDERING:

- Available in 1 gallon cans and 5 gallon buckets.
- Coverage is 100 - 300 square feet per gallon, per coat, depending on the type of surface and porosity.

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
1555 PAVER SEALER WB 1G	155501	1G	760428155514	14" x 14" x 8"	4	54 Cases
1555 PAVER SEALER WB 5G	155505	5G	760728155552	12" x 12" x 15"	1	36 Cases

STORAGE & HANDLING:

- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID: In case of skin contact**, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. **For eye contact**, flush immediately with large amounts of water, for at least 15 minutes. **If swallowed**, get medical attention immediately. **If inhalation causes physical discomfort**, move to fresh air. **If discomfort persists** or any breathing difficulty occurs, get medical help.

PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.**
- **Warning! Irritant!** Harmful if swallowed.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.

1555 PAVER SEALER - WATER BASED

PROPERTIES	
Weight per Gallon	8.56 lbs.
Color(s)	Clear
Gloss	Medium
VOC Content	94.7 Grams per Liter (cal.)
Viscosity	52 KU @ 75° F
Solid Content by Weight	28.4%
Solid Content by Volume	20%
Resin	100% Acrylic
Flash Point	None
Dry Time @ 70°F & 50% RH Drying times are influenced by ambient temperature and relative humidity.	To Touch: 2 Hours Vehicle Traffic: 3 Days Full Cure: 21 Days

- Do not apply to concrete where hydrostatic pressure is present or over 3 lbs. of moisture per 1000 sq. ft. ASTM F1869-04.
- Not intended for use over wood or areas of standing water.
- Check for a high pH, ASTM D4262 specification.

APPLICATION:

- Do not dilute.
- Do not apply if the threat of rain is imminent or if the air/surface temperature is expected to be below 50°F within the first 24 hours of application.
- Do not apply in extreme heat of day or in direct sunlight.
- Hand stir product thoroughly before application.
- Apply in one thin coat by brush, roller, fan tip pump sprayer or airless sprayer.
- Avoid heavy application resulting in runs, ponding, flood coating or puddling.
- One thin coat is recommended, do not apply multiple coats for danger of turning milky white by moisture contact.
- Some surfaces such as inclined driveways, garages, patios, steps etc. may require a slip resistant additive for safety. Add Anvil #9102 Talon Grip Slip Resistant Additive to the final coat.
- This product should not be used in place of a non-skid finish.
- We recommend that a parked car stand on cardboard until full cure.

DIRECTIONS FOR USE AND SURFACE PREPARATION:

- Proper preparation will ensure maximum adhesion, durability, and uniform coloration, ASTM D4258-83 Specification.
- The surface must be clean and free of all wax, grease, oil, dirt, acid, mildew, release agents and all other surface contaminants.
- Failure to remove grease, oil, soap or other contamination will interfere with adhesion of the Paver Sealer. New pavers should be swept clean to remove sand or dirt.
- Older pavers must be clean.
- To clean surface, scrub with a solution of 1/2 cup of TSP (Trisodium Phosphate) per gallon of clean hot water.
- Rinse thoroughly with a power washer.
- Previously sealed pavers should be examined closely to be sure that the previously sealed paver will accept the new application.
- Adheres to most sealers that are old and weathered away, but will not adhere to silicate or siloxane type sealers.
- Painted concrete surfaces should be mechanically abraded or acid etched before sealing, ASTM D4260 Specification. Use Anvil #1450 Concrete & Masonry Cleaner & Etcher.
- Rinse area thoroughly and allow drying COMPLETELY before sealing. A properly etched surface will have the feel of 120 grit sandpaper.
- Extremely hard, glossy or alkaline concrete may require stronger acid solutions or repeated etching.
- Concrete should be at least 45 days old to reduce the possibility of the occurrence of efflorescence.

CLEANUP:

- Soap and water.