



DESCRIPTION:

- Quality, gloss latex roof paint that provides good hiding, uniform coverage, ease of application and holds up well in the Sunbelt climate.
- Especially formulated for use on unglazed concrete tile, masonry shingle or properly primed metal roofing.
- Treated with fungicide to resist mildew growth and discoloration of the paint film. It's gloss finish helps keep roofs looking freshly painted longer.

ORDERING:

- Available in 5 gallon buckets only.
- Coverage is approximately 175 to 350 square feet per gallon, per coat at recommended dry film thickness 2 to 3 mils. Barrel tile roofs can reduce coverage up to 100 sq. ft. per gallon

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
SEE PRODUCT DETAILS ON PAGE 2						

STORAGE & HANDLING:

- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID: In case of skin contact**, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. **For eye contact**, flush immediately with large amounts of water, for at least 15 minutes. **If swallowed**, get medical attention immediately. **If inhalation causes physical discomfort**, move to fresh air. **If discomfort persists** or any breathing difficulty occurs, get medical help.

PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.**
- **Warning! Irritant!** Harmful if swallowed, when tinted, contains ethylene glycol which can cause severe kidney damage when ingested and has been shown to cause birth defects in laboratory animals.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.



WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

9980 SERIES ROOF-TEC TILE GUARD ACRYLIC ROOF COATING

PROPERTIES	
Weight per Gallon	10.3 lbs.
Color(s)	See chart below
Gloss	Gloss
VOC Content	97.5 Grams per Liter (cal.)
Viscosity	95 KU @ 75° F
Solid Content by Weight	48.6%
Solid Content by Volume	35.4%
Resin	Acrylic Latex
Flash Point	None
Dry Time @ 70°F & 50% RH Drying times are influenced by ambient temperature and relative humidity.	To Touch: 1/2 to 1 Hour To Recoat: 2 to 4 Hours Full Cure: 6 to 10 Days

- Apply a chlorine solution with a pressure cleaner or auxiliary sprayer to kill mildew or fungus spores. Rinse thoroughly.
- Prime bare metal with Anvil 1606 Rust Inhibitive Universal Primer or a quality acrylic rust encapsulating primer.

APPLICATION:

- Do not apply in direct sunlight. All roof surfaces must be dry. Apply starting at the top of the roof and working down
- Use brush, roller or spray to apply. Best results are obtained when using airless spray equipment.
- Two thin, uniform coats of paint will out-perform one heavy coat. Mix thoroughly prior to use.
- When working with more than one can of the same product, inter-mix to ensure color uniformity.
- Painted surface must be maintained by cleaning periodically with a mild chlorine solution.
- CAUTION: Roof surfaces may become extremely slippery when wet.

COLORS:

White Tint Base 9980	Brick Red 9981	Bronze Mum 9982	Tudor Brown 9983	Terra Cotta 9985
-------------------------	-------------------	--------------------	---------------------	---------------------

TINTING

- Universal Colorants

DIRECTIONS FOR USE AND SURFACE PREPARATION:

- To ensure a good bond to a sound substrate, all dust, dirt, soot, grease, calcium or salt film, loose sand or gravel, fungus, mildew, algae or other contamination must be removed.
- Previously applied paints that have deteriorated through age and are powdering, chalking, flaking, peeling or blistering must also be removed.
- The surface condition determines which cleaning method is required - washing, scraping, wire brushing or pressure cleaning or a combination may be required.

CLEANUP:

- Water

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
9980 TG GLOSS ROOF WHITE 5G	998005	5G	760428998050	12" x 12" x 15"	1	36 Cases
9981 TG GLOSS ROOF BRICK RED 5G	998105	5G	760428998159	12" x 12" x 15"	1	36 Cases
9982 TG GLOSS ROOF BRNZ MUM 5G	998205	5G	760428998258	12" x 12" x 15"	1	36 Cases
9983 TG GLOSS ROOF TUDOR BR 5G	998305	5G	760428998357	12" x 12" x 15"	1	36 Cases
9985 TG GLOSS ROOF TERRA COTTA 5G	998505	5G	760428998551	12" x 12" x 15"	1	36 Cases
9988 TG GLOSS ROOF DEEP TB 5G	998805	5G	760428998852	12" x 12" x 15"	1	36 Cases
9989 TG GLOSS ROOF ACCENT TB 5G	998905	5G	760428998852	12" x 12" x 15"	1	36 Cases