



DESCRIPTION:

- A water-based, non-yellowing clear coating for sealing concrete, pavers, Chattahoochee and exposed aggregate concrete, residential driveways, walkways patios and decks.
- Delivers a satin sheen when applied to a properly prepared surface and is highly resistant to the effects of hot automobile tires and water blushing. It is formulated for use on exterior/interior surfaces.
- Durable acrylic formula resists fading, scuffing, cracking, peeling and blistering.
- Milky white color in the can, but dries clear.

ORDERING:

- Available in 5 gallon buckets only.
- Coverage is 200 square feet per gallon, per coat, depending on the type of surface and porosity.

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
1320 CRYSTAL CLEAR SEALER WB 5G	132005	5G	760428132058	12" x 12" x 15"	1	36 Cases

STORAGE & HANDLING:

- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID: In case of skin contact**, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. **For eye contact**, flush immediately with large amounts of water, for at least 15 minutes. **If swallowed**, get medical attention immediately. **If inhalation causes physical discomfort**, move to fresh air. **If discomfort persists** or any breathing difficulty occurs, get medical help.

PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.**
- **Warning! Irritant!** Harmful if swallowed, when tinted, contains ethylene glycol which can cause severe kidney damage when ingested and has been shown to cause birth defects in laboratory animals.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.

1320 CRYSTAL CLEAR COAT WATER BASED SEALER

PROPERTIES	
Weight per Gallon	8.56 lbs.
Color(s)	Clear Satin Sheen
VOC Content	94.7 Grams per Liter (cal.)
Viscosity	52 KU @ 75° F
Solid Content by Weight	28%
Solid Content by Volume	21%
Resin	100% Acrylic
Flash Point	None
Dry Time @ 70°F & 50% RH Drying times are influenced by ambient temperature and relative humidity.	To Touch: 2 Hours Vehicle Traffic: 3 Days Full Cure: 21 Days

- Avoid heavy application resulting in runs, ponding, flood coating or puddling.
- One thin coat is recommended, do not apply multiple coats for danger of turning milky white by moisture contact.
- Some surfaces such as inclined driveways, patios, steps etc. may require a slip resistant additive for safety. Add Anvil #9102 Talon Grip Slip Resistant Additive to the final coat.
- This product should not be used in place of a non-skid finish.
- We recommend that a parked car stand on cardboard until full cure.

CLEANUP:

- Soap and water.

DIRECTIONS FOR USE AND SURFACE PREPARATION:

- Proper preparation will ensure maximum adhesion, durability, and uniform coloration.
- The surface must be clean and free of all wax, grease, oil, dirt, acid, mildew, release agents and all other surface contaminants.
- Failure to remove grease, oil, soap or other contamination will interfere with adhesion of the Crystal Clear Coat.
- To clean surface and etch, we recommend using Anvil #1450 Concrete & Masonry Cleaner & Etcher.
- Rinse area thoroughly and allow drying COMPLETELY before sealing.
- Concrete should be at least 45 days old to reduce the possibility of the occurrence of efflorescence.
- Do not apply to surfaces where hydrostatic pressure is present or over 3 lbs. of moisture per 1000 sq. ft. ASTM F1869-04.
- Not intended for use over wood or areas of standing water.

APPLICATION:

- Do not dilute.
- Do not apply if the threat of rain is imminent or if the air/surface temperature is expected to be below 50°F within the first 24 hours of application.
- Do not apply in extreme heat of day or in direct sunlight.
- Hand stir product thoroughly before application.
- Apply in one thin coat by brush, roller, fan tip pump sprayer or airless sprayer.