



DESCRIPTION:

- Fast drying, water clean up, environmentally friendly, Specially formulated "two in one" interior dry wall primer that ensures the finish coat of paint will look its best.
- Primes, covers and fills the differences between variations of gypsum board paper and joint compound finishes.
- Replaces the two-step finishing process of joint compound skim coating the entire surface and pre-paint priming, to a level 5 finish.
- Adds a slight texture to dry wall that helps to equalize the rough, uneven, and minor surface imperfections found in new construction dry wall installations.
- Forms a tight dry film with excellent hold out characteristic that deliver a uniform sheen and appearance of the finished decorative paint coat.

ORDERING:

- Available in 5 gallon buckets only.
- Coverage is 200 square feet at 8 wet mils film thickness. Less at higher wet mils.

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
1820 TEXWALL ULTRA HIGH BUILD 5G	182005	5G	760428182053	12" x 12" x 15"	1	36 Cases

STORAGE & HANDLING:

- **CONTAINS SOLVENTS, WHICH CAN CAUSE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.**
- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID:** In case of skin contact, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. For eye contact, flush immediately with large amounts of water, for at least 15 minutes. If swallowed, get medical attention immediately. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help.

PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.**
- **Warning! Irritant!** Harmful if swallowed.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.



WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

1820 TEXWALL HIGH BUILD RESURFACER / PRIMER

PROPERTIES	
Weight per Gallon	12.42 lbs.
Color(s)	High Hide White, tintable up to 2 oz. universal colorant per gallon
Gloss	Matte
VOC Content	82.5 Grams per Liter (cal.)
Viscosity	115-118 KU @ 75° F
Solid Content by Weight	61.9%
Solid Content by Volume	43.1%
Pigment by weight	49.0%
Vehicle by weight	51.0
Resin	100% Vinyl Acrylic
Dry Time @ 77° F & 50% RH Drying times are influenced by ambient temperature and relative humidity.	To Touch: 1 Hour To Recoat: 8 Hours

- Coverage will vary greatly depending upon method of application, surface condition, and finish level desired according to ASTM C-840.

A test application is recommended to determine actual coverage under specific job conditions and board conditions.

APPLICATION:

- Apply by suitable airless spray unit at package consistency.
- The airless sprayer should be capable of delivering more than 1 gallon a minute.
- Remove all in-line filters.
- Use a 3/8" material hose and a 23 to 31 tip at 1700 to 3000 psi. Always work to a wet edge.
- Varying orifice size, pressure and technique will influence finish appearance. Experimentation and test application are recommended.
- Once a procedure has been determined to achieve the desired results all changes including applicator should be avoided until a different wall or natural breaking point has been reached.

DIRECTIONS FOR USE AND SURFACE PREPARATION:

- Process is used on interior new construction drywall, cured plaster or concrete surfaces.
- The prime finish produced by this product is excellent for walls in homes, hotels, motels, offices and apartments that require a uniform beautifully finished wall appearance.

SURFACE PREPARATION:

- Substrate must be clean, dry, sound and PAINT READY. Wall surfaces should be dry, free of dust, grime or other contaminants that could interfere with the bonding characteristics of Anvil TexWall High Build Resurfacer/Primer.
- Product, air and surface temperatures must be maintained at a minimum of 50° F.
- New masonry or plaster must be allowed to cure for at least 30 days.
- Repair any significant voids, cracks and fastener holes.
- Check all corner beads or exposed nail and screw heads that are likely to produce rust in the future and prime with a stain blocking metal primer.
- On walls stained from mildew, water, grease or other causes, a stain blocking primer should be applied to reduce flashing.

COVERAGE:

- Coverage is 200 square feet at 8 wet mils film thickness. Less at higher wet mils.

CLEANUP:

- Clean all equipment immediately after use with warm soapy water.