



#### DESCRIPTION:

- Specially formulated using styrene acrylic resins for use on unpainted horizontal concrete and asphalt surfaces such as driveways, garage floors, patios, walkways, decks and sidewalks.
- A high resin formula for bare horizontal concrete surfaces, but NOT for use on wood, brick pavers, stamped concrete, epoxy or polyurethane coatings.
- Low odor, water reducible and nonflammable.
- Hard satin gloss finish that is water resistance.
- Good resistance to most solvents and some chemicals, oil and gasoline spills.
- Brush, roller or spray applications.

#### ORDERING:

- Available in 1 gallon cans and 5 gallon buckets.
- Coverage is approximately 300 to 500 square feet per gallon, per coat, depending on the type of surface and porosity.

| PRODUCT                  | NO     | SIZE | UPC          | Case Size (L x W x H) | Case Qty. | Pallet Qty. |
|--------------------------|--------|------|--------------|-----------------------|-----------|-------------|
| 1330 ULTRASEAL CL ACR 1G | 133001 | 1G   | 760428133017 | 14" x 14" x 8"        | 4         | 54 Cases    |
| 1330 ULTRASEAL CL ACR 5G | 133005 | 5G   | 760428133055 | 12" x 12" x 15"       | 1         | 36 Cases    |

#### STORAGE & HANDLING:

- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID: In case of skin contact**, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. **For eye contact**, flush immediately with large amounts of water, for at least 15 minutes. **If swallowed**, get medical attention immediately. **If inhalation causes physical discomfort**, move to fresh air. **If discomfort persists** or any breathing difficulty occurs, get medical help.

#### PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).**
- **Warning! Irritant!** Harmful if swallowed, when tinted, contains ethylene glycol which can cause severe kidney damage when ingested and has been shown to cause birth defects in laboratory animals.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.

## 1330 ULTRASEAL CONCRETE FLOOR AND DRIVEWAY SEALER

| <b>PROPERTIES</b>   |   |
|---|---|
| Weight per Gallon   | 9.45 lbs  |
| Color(s)  | Clear   |
| Gloss   | Low Luster  |
| VOC Content   | 61.1 Grams per Liter (cal.)   |
| Viscosity   | 78 KU @ 75° F   |
| Solid Content by Weight   | 33.0%   |
| Solid Content by Volume   | 30.0%   |
| Resin   | 100% Acrylic  |
| Flash Point   | None  |
| Dry Time @ 70°F & 50% RH<br>Drying times are influenced<br>by ambient temperature and<br>relative humidity. | To Touch: 1/2 to 1 Hour<br>To Recoat: 1 to 2 Hours<br>Foot Traffic: 3 to 4 Hours<br>Vehicle Traffic: 72 Hours |

- Add Anvil #9102 Skid Resistant Additive to the final coat of UltraSeal. This product should not be used in place of a nonskid finish.

### **CLEANUP:**

- Water

### **DIRECTIONS FOR USE AND SURFACE PREPARATION:**

- Remove all dirt, efflorescence, grease, oil, waxes, silicone products and other foreign material that would interfere with the adhesion of the sealer.
- Uncoated smooth steel troweled concrete floors (surfaces with no porosity) must be totally cured, etched, neutralized, rinsed and cleaned for proper adhesion and durability of the sealer.
- For cleaning/etching, use Anvil #1450 Concrete & Masonry Cleaner & Etcher.
- Rinse area thoroughly and allow drying COMPLETELY before sealing. A properly prepared surface will have the feel of 120 grit sandpaper.

### **APPLICATION:**

- Do not dilute
- Do not apply if the threat of rain is imminent or if the air/surface temperature is expected to be below 50° F within the first 24 hours of application.
- Hand stir product thoroughly before application.
- Apply in thin multiple coats by brush, roller or spray. Avoid heavy application resulting in runs, ponding or puddling. Two thin coats are recommended depending on the surface being coated and the gloss desired.
- Some surfaces such as inclined driveways, garages, patios, steps, etc. may require a slip resistant additive for safety.