



DESCRIPTION:

- Water-based, non-yellowing clear coating for glazing and sealing exposed stone surfaces that delivers a medium gloss when applied to a properly prepared surface.
- Formulated for use on exterior/interior stone and concrete surfaces such as patios, walkways, decks, decks and sidewalks. Not intended for use over wood or areas of standing water.
- Resistant to mild automotive chemicals, oil, grease and gasoline. Its' durable acrylic formula also resists fading, scuffing, cracking, peeling and blistering. Light tan color in the can, but dries crystal clear.

ORDERING:

- Available in 1 gallon cans and 5 gallon buckets.
- Coverage is approximately 100 square feet per gallon, per coat, depending on the size of stone and porosity.

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
1550 CHATTAHOOCHEEE SLR WB 1G	155001	1G	760428155019	14" x 14" x 8"	4	54 Cases
1550 CHATTAHOOCHEEE SLR WB 5G	155005	5G	760428155057	12" x 12" x 15"	1	36 Cases

STORAGE & HANDLING:

- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID: In case of skin contact**, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. **For eye contact**, flush immediately with large amounts of water, for at least 15 minutes. **If swallowed**, get medical attention immediately. **If inhalation causes physical discomfort**, move to fresh air. **If discomfort persists** or any breathing difficulty occurs, get medical help.

PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.**
- **Warning! Irritant!** Harmful if swallowed.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.

1550 CHATTAHOOCHEE STONE SEALER - WATER BASED

PROPERTIES	
Weight per Gallon	8.56 lbs.
Color(s)	Crystal Clear
Gloss	Medium
VOC Content	94.7 Grams per Liter (cal.)
Viscosity	78 KU @ 75° F
Solid Content by Weight	28.4%
Solid Content by Volume	20%
Resin	100% Acrylic
Flash Point	None
Dry Time @ 70°F & 50% RH Drying times are influenced by ambient temperature and relative humidity.	To Touch: 2 Hours Vehicle Traffic: 3 Days Full Cure: 21 Days

APPLICATION:

- Do not dilute.
- Do not apply if the threat of rain is imminent or if the air/surface temperature is expected to be below 50°F within the first 24 hours of application.
- Do not apply in extreme heat or in direct sunlight.
- We recommend that a parked car stand on cardboard until full cure.
- Hand stir product thoroughly before application. Apply in one thin coat by brush, roller, fan tip pump sprayer or airless sprayer. Avoid heavy application resulting in runs, ponding, flood coating or puddling.
- One thin coat is recommended, do not apply multiple coats for danger of turning milky white by moisture contact.
- Some surfaces such as inclined driveways, garages, patios, steps etc. may require a slip resistant additive for safety. Add Anvil #9102 Talon Grip Slip Resistant Additive to the final coat.

DIRECTIONS FOR USE AND SURFACE PREPARATION:

- Proper preparation will ensure maximum adhesion, durability, and uniform coloration, ASTM D4258-83 Specification. This product should not be used in place of a non-skid finish.
- Do not apply to exposed stone concrete where hydrostatic pressure is present or over 3 lbs. of moisture per 1000 sq. ft. ASTM F1869-04.
- Exposed stone concrete should be at least 45 days old to reduce the possibility of the occurrence of efflorescence.
- Surface must be clean and free of all wax, grease, oil, dirt, acid, mildew, release agents and all other surface contaminants. Failure to remove grease, oil, soap or other contamination will interfere with adhesion of the sealer.
- To clean surface, scrub with a solution of 1/2 cup of TSP (Trisodium Phosphate) per gallon of clean hot water. Rinse thoroughly with a power washer.
- Anvil Chattahoochee Stone Sealer will adhere to most sealers that are old and weathered away, but will not adhere to silicate or siloxane type sealers.
- Use Anvil #1450 Concrete & Masonry Cleaner & Etcher. Rinse area thoroughly and allow drying COMPLETELY before sealing.

CLEANUP:

- Soap and water