



## ***SUPER LIFE® FARMTRACT 15W-40 CF-4***

### **AGRICULTURAL HEAVY DUTY ENGINE OIL**

***SUPER LIFE® FARMTRACT 15W-40 CF-4*** is high quality oil specially formulated for maximum engine protection under very severe conditions of turbocharge or naturally aspirated engines used in tractors, combine harvesters, soil preparation machines, off road equipment and most farm machines where engine oil 15W-40 API CF-4/CF is required. They are formulated from high quality base stocks and additive packages with excellent detergent property, good anti-wear and anti-oxidation. The use of these oils minimizes the formation of carbon and sludge deposits that is caused by frequent stop- and- go service.

#### **APPLICATIONS:**

***SUPER LIFE® FARMTRACT 15W-40 CF-4*** is recommended for heavy duty diesel engines of trucks, tractors, harvesters, construction equipment, passenger cars, ships and boats on the river and on the sea and diesel generators .

***SUPER LIFE® FARMTRACT 15W-40 CF-4*** meets technical requirements of the following engine manufacturers : KUBOTA, JOHN DEERE, AGCO, CNH, NEW HOLLAND, SAME DEUTZ-FAHR, CUMMINS, CATERPILLAR, INTERNATIONAL, DETROIT DIESEL, KOMATSU, ISUZU, NISSAN, MITSUBISHI, MERCEDES, TOYOTA, HYUNDAI, KIA, etc.

API CF-4/CF, CD/SF	API GL-4	ACEA E2/E1	CCMC D4/PD2
Caterpillar TO-2	John Deere J27	Ford New Holland M2C 159B	
MIL-L- 2104E	MIL-L- 46152E	ZF TE-ML 06B/06C/07B	

#### **BENEFITS:**

- Fuel saving and reduces maintenance expenses for machines, engines .
- Very long oil changing period
- Resist oil thickening and the formation of carbon, varnish and sludge deposits causing by high temperature and high speed . Keeps engines always clean .
- Good protection of vital engine parts, resists corrosion effect in fuel combustion cycle and keeps the viscosity unchanged at high temperature .
- Prolong engine life.

#### **TYPICAL CHARACTERISTICS**

Test	Method	Typical results
SAE Viscosity grade	SAE J300	15W-40
API Gravity	ASTM D 287	27.85

Specific gravity @ 15.6°C (60°F)	ASTM D1298	0.888
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D445	108.4 14.5
Viscosity Index	ASTM D2270	137
Flash Point, °C (°F)	ASTMD92	220 (428)
Pour Point, °C (°F)	ASTM D97	-27 (-17)
Total Base Number, mgKOH/g	ASTM D2896	9.0

*The above characteristics are average values based on recent production. Minor variations, which do not affect product performance, are to be expected in normal manufacture.*

**WARNING:**

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS Number 12021 database on our website at [www.amtecol.com](http://www.amtecol.com)

**OR scan the code for a direct link**

