



SUPER LIFE® FARMTRACT 15W-40 CI-4

AGRICULTURAL HEAVY DUTY ENGINE OIL

SUPER LIFE® FARMTRACT 15W-40 CI-4 is high performance lubricant specially formulated for maximum engine protection under very severe conditions of today's turbocharge, naturally aspirated and supercharged engines, including diesel engines utilizing Exhaust Gas Recirculation (EGR) used in tractors, combine harvesters, soil preparation machines, off road equipment and most farm machines where engine oil 15W-40 API CI-4/CF-4/CF is required. They are formulated with premium base oils and the latest additive technology with excellent detergent property, good anti-wear and anti-oxidation. The use of these oils minimizes the formation of carbon and sludge deposits that is caused by frequent stop- and- go service.

APPLICATIONS:

SUPER LIFE® FARMTRACT 15W-40 CI-4 is recommended for heavy duty diesel engines of trucks, tractors, harvesters, construction equipment, passenger cars, ships and boats on the river and on the sea and diesel generators .

SUPER LIFE® FARMTRACT 15W-40 CI-4 meets technical requirements of the following engine manufacturers : KUBOTA, JOHN DEERE, AGCO, CNH, NEW HOLLAND, SAME DEUTZ-FAHR, CUMMINS, CATERPILLAR, INTERNATIONAL, DETROIT DIESEL, KOMATSU, ISUZU, NISSAN, MITSUBISHI, MERCEDES, TOYOTA, HYUNDAI, KIA, etc.

API CI-4/CH-4/CF-4/CF

ACEA E7/E6/E5

MB 228.3/228.1

Caterpillar ECF-2/ECF-1a/TO-2

John Deere JDQ 78A

Ford New Holland NH 330H

Case MS 1121

Cummins CES 20076/20077/20078

Deutz DQC III-10

BENEFITS:

- Minimize piston and combustion chamber deposits.
- Fight sludge and varnish.
- Excellent protection against engine wear due to soot.
- Fuel economy, oil economy
- Maintain oil film under conditions of high temperature and high stress. Protect moving parts from friction, wear and engine destroying metal-to-metal contact.
- Excellent oxidation, foam, corrosion inhibition
- Provide faster, safe starts during extreme low temperatures and increase thermal and oxidation stability at extreme high temperatures.
- Extend engine life

TYPICAL CHARACTERISTICS

Test	Method	Typical results
SAE Viscosity grade	SAE J300	15W-40
API Gravity	ASTM D 287	28.93
Specific gravity @ 15.6°C (60°F)	ASTM D1298	0.882
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D445	113.0 15.2
Viscosity Index	ASTM D2270	140
Flash Point, °C (°F)	ASTMD92	224 (435)
Pour Point, °C (°F)	ASTM D97	-27 (-17)
Total Base Number, mgKOH/g	ASTM D2896	10.0

The above characteristics are average values based on recent production. Minor variations, which do not affect product performance, are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS Number 12021 database on our website at www.amtecol.com

OR scan the code for a direct link

