



SUPER LIFE® SYNTHETIC RACING 4-STROKE ENGINE OILS

SUPER LIFE® SYNTHETIC RACING 4-STROKE ENGINE OILS are premium quality synthetic lubricants specially engineered for today's 4-stroke single cylinder, multi-valve racing engines. They are formulated with Synthetic base stocks and a unique additive package chosen for exceptional wear protection, sludge and varnish resistance, and thermal stability. They provide maximum horsepower and give a perfect lubrication to racing 4T engines used at very high and continuously changing loads as they occur at racing conditions.

APPLICATIONS:

SUPER LIFE® SYNTHETIC RACING 4-STROKE ENGINE OILS are recommended for all types of 4-stroke motorcycles of manufacturers including HARLEY-DAVIDSON, HONDA, BMW, SUZUKI, YAMAHA, KAWASAKI, MOTO GUZZI, TRIUMPH, etc. Ideal for large capacity (greater than 600cc) European motorcycles in severe service operation such as in competition and in high ambient temperatures.

API SM
JASO MA 2

BENEFITS:

- Help engine reach maximum performance and power, quick starting up .
- Controlled frictional properties eliminate clutch slippage leading to increased power/ fuel economy and improves drivability. Non-friction modified to maintain clutch effectiveness.
- Protect well heavy loaded parts in very severe conditions of operating : high speed, high temperature, rough roads .
- Anti-wear properties, lower corrosion and friction. Provide excellent protection for transmissions and wet clutches .
- Help reduce foaming and air-entrainment in high speed engines.
- Help engine running smoothly and freshly .
- Excellent fuel saving, lengthen the oil changing intervals, economize everything . Prolong engine life .
- Provide good characteristics in harmful deposit control to help keep the engine and gearbox running cleaner and provides good gearbox protection for incorporated gearboxes .

TYPICAL CHARACTERISTICS

Test	Method	Typical Results				
		5W-40	10W-40	15W-50	20W-50	20W-60
SAE Viscosity grade	SAE J300	5W-40	10W-40	15W-50	20W-50	20W-60
API Gravity	ASTM D287	34.77	34.38	33.03	31.52	31.14
Specific gravity @ 15.6°C (60°F)	ASTM D1298	0.851	0.853	0.860	0.868	0.870

Viscosity @ 40°C cSt @ 100°C cSt	ASTM D445	94 14.90	90.5 14.70	120 18.5	125 18.2	173 24
Viscosity Index	ASTM D2270	166	170	173	163	168
Flash Point, °C (°F)	ASTM D92	230(446)	230(446)	232(449.6)	235(455)	235(455)
Pour Point, °C (°F)	ASTM D97	-42(-43.6)	-42(-43.6)	-40(-40)	-35(-31)	-35(-31)
Noack , wt%	ASTM D5800	8	7.5	7.1	6.7	6.3

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS Number 12022 database on our website at www.amtecol.com
OR scan the code for a direct code

