

According to OSHA Hazard Communication Standard 29CFR 1910.1200  
(HCS 2012)

<b>LA LMM-6012</b>		<b>GSLA_LMM-6012 Black ScreenPrintable 500g</b>	
Product specification	<b>RS_FP_305653</b>	Revision Date	<b>02/20/2020</b>
Version	<b>2.3</b>	Print Date	<b>02/26/2020</b>
Material number	<b>1407094</b>	Page	Page 1 of 14

## SECTION 1. IDENTIFICATION

Product name : **LA LMM-6012**  
GSLA\_LMM-6012 Black ScreenPrintable 500g

Material number : **1407094**

### Manufacturer or supplier's details

Company name of supplier : Ferro Corporation

Address : 6060 Parkland Blvd. Suite 250  
Mayfield Heights OH 44124-4185

Telephone : (216) 875-5600

### Emergency telephone number

In-Country Number : (800)424-9300

CHEMTREC Global Number : +(1)-703-527-3887 (Call Collect)

### Recommended use of the chemical and restrictions on use

Recommended use : Consult the technical guidelines for the use of this  
substance/mixture.

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

Acute toxicity (Oral) : Category 4

Eye irritation : Category 2A

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 1  
- single exposure

Specific target organ toxicity : Category 3 (Respiratory system)  
- single exposure

Specific target organ toxicity : Category 1  
- repeated exposure

### GHS Label element

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>LA LMM-6012</b>		<b>GSLA_LMM-6012 Black ScreenPrintable 500g</b>	
Product specification	<b>RS_FP_305653</b>	Revision Date	<b>02/20/2020</b>
Version	<b>2.3</b>	Print Date	<b>02/26/2020</b>
Material number	<b>1407094</b>	Page	<b>Page 2 of 14</b>

Hazard pictograms	:																																	
Signal word	:	Danger																																
Hazard statements	:	<table border="0"> <tr> <td style="vertical-align: top;">H302</td> <td style="vertical-align: top;">Harmful if swallowed.</td> </tr> <tr> <td style="vertical-align: top;">H319</td> <td style="vertical-align: top;">Causes serious eye irritation.</td> </tr> <tr> <td style="vertical-align: top;">H335</td> <td style="vertical-align: top;">May cause respiratory irritation.</td> </tr> <tr> <td style="vertical-align: top;">H361</td> <td style="vertical-align: top;">Suspected of damaging fertility or the unborn child.</td> </tr> <tr> <td style="vertical-align: top;">H370</td> <td style="vertical-align: top;">Causes damage to organs.</td> </tr> <tr> <td style="vertical-align: top;">H372</td> <td style="vertical-align: top;">Causes damage to organs through prolonged or repeated exposure.</td> </tr> </table>	H302	Harmful if swallowed.	H319	Causes serious eye irritation.	H335	May cause respiratory irritation.	H361	Suspected of damaging fertility or the unborn child.	H370	Causes damage to organs.	H372	Causes damage to organs through prolonged or repeated exposure.																				
H302	Harmful if swallowed.																																	
H319	Causes serious eye irritation.																																	
H335	May cause respiratory irritation.																																	
H361	Suspected of damaging fertility or the unborn child.																																	
H370	Causes damage to organs.																																	
H372	Causes damage to organs through prolonged or repeated exposure.																																	
Precautionary statements	:	<table border="0"> <tr> <td colspan="2"><b>Prevention:</b></td> </tr> <tr> <td style="vertical-align: top;">P201</td> <td style="vertical-align: top;">Obtain special instructions before use.</td> </tr> <tr> <td style="vertical-align: top;">P202</td> <td style="vertical-align: top;">Do not handle until all safety precautions have been read and understood.</td> </tr> <tr> <td style="vertical-align: top;">P260</td> <td style="vertical-align: top;">Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.</td> </tr> <tr> <td style="vertical-align: top;">P264</td> <td style="vertical-align: top;">Wash skin thoroughly after handling.</td> </tr> <tr> <td style="vertical-align: top;">P270</td> <td style="vertical-align: top;">Do not eat, drink or smoke when using this product.</td> </tr> <tr> <td style="vertical-align: top;">P271</td> <td style="vertical-align: top;">Use only outdoors or in a well-ventilated area.</td> </tr> <tr> <td style="vertical-align: top;">P280</td> <td style="vertical-align: top;">Wear protective gloves/ protective clothing/ eye protection/ face protection.</td> </tr> <tr> <td colspan="2"><b>Response:</b></td> </tr> <tr> <td style="vertical-align: top;">P301 + P312 + P330</td> <td style="vertical-align: top;">IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.</td> </tr> <tr> <td style="vertical-align: top;">P304 + P340 + P312</td> <td style="vertical-align: top;">IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.</td> </tr> <tr> <td style="vertical-align: top;">P305 + P351 + P338</td> <td style="vertical-align: top;">IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</td> </tr> <tr> <td style="vertical-align: top;">P307 + P311</td> <td style="vertical-align: top;">IF exposed: Call a POISON CENTER or doctor/ physician.</td> </tr> <tr> <td style="vertical-align: top;">P337 + P313</td> <td style="vertical-align: top;">If eye irritation persists: Get medical advice/ attention.</td> </tr> <tr> <td colspan="2"><b>Storage:</b></td> </tr> <tr> <td style="vertical-align: top;">P403 + P233</td> <td style="vertical-align: top;">Store in a well-ventilated place.</td> </tr> </table>	<b>Prevention:</b>		P201	Obtain special instructions before use.	P202	Do not handle until all safety precautions have been read and understood.	P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.	P264	Wash skin thoroughly after handling.	P270	Do not eat, drink or smoke when using this product.	P271	Use only outdoors or in a well-ventilated area.	P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.	<b>Response:</b>		P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.	P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.	P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	P307 + P311	IF exposed: Call a POISON CENTER or doctor/ physician.	P337 + P313	If eye irritation persists: Get medical advice/ attention.	<b>Storage:</b>		P403 + P233	Store in a well-ventilated place.
<b>Prevention:</b>																																		
P201	Obtain special instructions before use.																																	
P202	Do not handle until all safety precautions have been read and understood.																																	
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.																																	
P264	Wash skin thoroughly after handling.																																	
P270	Do not eat, drink or smoke when using this product.																																	
P271	Use only outdoors or in a well-ventilated area.																																	
P280	Wear protective gloves/ protective clothing/ eye protection/ face protection.																																	
<b>Response:</b>																																		
P301 + P312 + P330	IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.																																	
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.																																	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.																																	
P307 + P311	IF exposed: Call a POISON CENTER or doctor/ physician.																																	
P337 + P313	If eye irritation persists: Get medical advice/ attention.																																	
<b>Storage:</b>																																		
P403 + P233	Store in a well-ventilated place.																																	

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>LA LMM-6012</b>		<b>GSLA_LMM-6012 Black ScreenPrintable 500g</b>	
Product specification	RS_FP_305653	Revision Date	02/20/2020
Version	2.3	Print Date	02/26/2020
Material number	1407094	Page	Page 3 of 14

Keep container tightly closed.

**Disposal:**  
P501

Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	: Mixture
Chemical nature	: silicatic material, inorganic metal-nonmetal compound, glycol ether/-acetate, inorganic salt

### Hazardous components

Chemical Name	CAS-No.	Concentration (%)
Trade Secret Molybdenum Compound	Not Assigned	>= 30 - < 50
2-(2-butoxyethoxy)ethanol	112-34-5	>= 30 - < 50
Trade Secret Silicated compound	Not Assigned	>= 5 - < 10
Trade Secret Vanadium Compound	Not Assigned	>= 5 - < 10

## SECTION 4. FIRST AID MEASURES

General advice	: Consult a physician.
If inhaled	: Remove to fresh air. If unconscious place in recovery position and seek medical advice. Never give anything by mouth to an unconscious person.
In case of skin contact	: Wash off immediately with soap and plenty of water. If a person feels unwell or symptoms of skin irritation appear, consult a physician.
In case of eye contact	: Rinse immediately with plenty of water and seek medical advice.
If swallowed	: Do NOT induce vomiting. Rinse immediately with plenty of water and seek medical advice.
Most important symptoms and effects, both acute and delayed	: Harmful if swallowed. Causes serious eye irritation. May cause respiratory irritation. Suspected of damaging fertility or the unborn child. Causes damage to organs. Causes damage to organs through prolonged or repeated

According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>LA LMM-6012</b>		<b>GSLA_LMM-6012 Black ScreenPrintable 500g</b>	
Product specification	<b>RS_FP_305653</b>	Revision Date	<b>02/20/2020</b>
Version	<b>2.3</b>	Print Date	<b>02/26/2020</b>
Material number	<b>1407094</b>	Page	<b>Page 4 of 14</b>

exposure.

## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific hazards during firefighting : Exposure to decomposition products may be a hazard to health.  
Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation.  
Follow safe handling advice and personal protective equipment recommendations.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
Prevent product from entering drains.
- Methods and materials for containment and cleaning up : Sweep up and shovel into suitable containers for disposal.  
Clean contaminated floors and objects thoroughly while observing environmental regulations.

## SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not get in eyes or mouth or on skin.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Do not use in areas without adequate ventilation.  
Keep away from heat and sources of ignition.
- Conditions for safe storage : Keep in a dry, cool and well-ventilated place.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

**LA LMM-6012** **GS LA LMM-6012 Black ScreenPrintable 500g**

Product specification	<b>RS_FP_305653</b>	Revision Date	<b>02/20/2020</b>
Version	<b>2.3</b>	Print Date	<b>02/26/2020</b>
Material number	<b>1407094</b>	Page	Page 5 of 14

Trade Secret Molybdenum Compound	Not Assigned	TWA	5 mg/m3 (Molybdenum)	OSHA Z-1
		TWA (Respirable fraction)	0.5 mg/m3 (Molybdenum)	ACGIH
		TWA	5 mg/m3 (Molybdenum)	OSHA P0
2-(2-butoxyethoxy)ethanol	112-34-5	TWA (Inhalable fraction and vapor)	10 ppm	ACGIH
Trade Secret Silicated compound	Not Assigned	TWA (Respirable fraction)	3 mg/m3	ACGIH
		TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Respirable)	3 mg/m3	NIOSH REL
		TWA (respirable dust fraction)	3 mg/m3	OSHA P0
Trade Secret Vanadium Compound	Not Assigned	C (Dust)	0.05 mg/m3 (Vanadium)	NIOSH REL
		C (Fumes)	0.05 mg/m3 (Vanadium)	NIOSH REL

**Engineering measures** : Apply technical measures to comply with the occupational exposure limits.  
Provide adequate ventilation.

**Personal protective equipment**

Respiratory protection : When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hand protection  
Material : Protective gloves

Eye protection : Safety glasses with side-shields  
Ensure that eyewash stations and safety showers are close to the workstation location.

Protective measures : Wear suitable protective equipment.  
When using do not eat, drink or smoke.  
Wear suitable protective equipment.  
Avoid contact with skin.  
When using do not eat, drink or smoke.

Hygiene measures : Remove contaminated clothing and protective equipment before entering eating areas.

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200  
(HCS 2012)

<b>LA LMM-6012</b>		<b>GSLA_LMM-6012 Black ScreenPrintable 500g</b>	
Product specification	<b>RS_FP_305653</b>	Revision Date	<b>02/20/2020</b>
Version	<b>2.3</b>	Print Date	<b>02/26/2020</b>
Material number	<b>1407094</b>	Page	Page 6 of 14

Wash hands before breaks and immediately after handling the product.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Colour	: black
Odour	: characteristic
Odour Threshold	: No data available
pH	: No data available
Melting point/range	: No data available
Boiling point/boiling range	: No data available
Flash point	: 105 °C Method: ASTM D 93, Pensky-Martens closed cup
Evaporation rate	: No data available
Burning rate	: No data available
Upper explosion limit	: 5.9 %(V)
Lower explosion limit	: 0.9 %(V)
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Bulk density	: No data available
Solubility(ies)	
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: Not determined
Decomposition temperature	: No data available

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>LA LMM-6012</b>		<b>GSLA_LMM-6012 Black ScreenPrintable 500g</b>	
Product specification	<b>RS_FP_305653</b>	Revision Date	<b>02/20/2020</b>
Version	<b>2.3</b>	Print Date	<b>02/26/2020</b>
Material number	<b>1407094</b>	Page	<b>Page 7 of 14</b>

---

Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Refractive index	:	No data available
Volatile organic compounds (VOC) content	:	The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489): This product does not contain any VOC exemptions listed under the U.S. Clean Air Act Section 450.

---

## SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Stable under recommended storage conditions.
Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed.
Hazardous decomposition products	:	Stable under normal conditions.

---

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

inhalation (dust/mist/fume)

inhalation (vapour)

Skin

Eye contact

Ingestion

### Acute toxicity

Harmful if swallowed.

#### Product:

Acute oral toxicity	:	Acute toxicity estimate: 1,389 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Remarks: No data available
Acute dermal toxicity	:	Acute toxicity estimate: > 5,000 mg/kg Method: Calculation method

#### Components:

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

LA LMM-6012		GSLA_LMM-6012 Black ScreenPrintable 500g	
Product specification	RS_FP_305653	Revision Date	02/20/2020
Version	2.3	Print Date	02/26/2020
Material number	1407094	Page	Page 8 of 14

### **Trade Secret Molybdenum Compound:**

- Acute oral toxicity : LD50 (Rat, male and female): 4,461 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes
- Acute inhalation toxicity : LC50 (Rat, male and female): > 5,840 mg/m<sup>3</sup>  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Target Organs: Mucous membranes  
GLP: yes  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: No adverse effect has been observed in acute toxicity tests.
- Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes  
Assessment: The substance or mixture has no acute dermal toxicity

### **2-(2-butoxyethoxy)ethanol:**

- Acute oral toxicity : LD50 Oral (Rat): 5,660 mg/kg
- Acute dermal toxicity : LD50 Dermal (Rabbit, male): 2,764 mg/kg  
Method: OECD Test Guideline 402

### **Trade Secret Vanadium Compound:**

- Acute oral toxicity : LD50 Oral (Rat): 98 mg/kg

### **Skin corrosion/irritation**

Not classified based on available information.

#### **Components:**

##### **Trade Secret Molybdenum Compound:**

Species: Rabbit  
Exposure time: 4 h  
Assessment: No skin irritation  
Method: OECD Test Guideline 404  
Result: No skin irritation  
GLP: yes

##### **2-(2-butoxyethoxy)ethanol:**

Species: Rabbit  
Exposure time: 1 h  
Method: OECD Test Guideline 404  
Result: Mild skin irritation

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>LA LMM-6012</b>		<b>GSLA_LMM-6012 Black ScreenPrintable 500g</b>	
Product specification	<b>RS_FP_305653</b>	Revision Date	<b>02/20/2020</b>
Version	<b>2.3</b>	Print Date	<b>02/26/2020</b>
Material number	<b>1407094</b>	Page	<b>Page 9 of 14</b>

### **Components:**

#### ***Trade Secret Molybdenum Compound:***

Species: Rabbit  
 Result: Irritating to eyes.  
 Assessment: Irritating to eyes.

#### ***2-(2-butoxyethoxy)ethanol:***

Species: Rabbit  
 Result: Eye irritation  
 Exposure time: 72 h  
 Method: OECD Test Guideline 405  
 GLP: no

### **Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.  
 Respiratory sensitisation: Not classified based on available information.

### **Germ cell mutagenicity**

Not classified based on available information.

### **Carcinogenicity**

Not classified based on available information.

#### **IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### **OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### **Reproductive toxicity**

Suspected of damaging fertility or the unborn child.

### **STOT Specific Target Organ Toxicity - single exposure**

May cause respiratory irritation.  
 Causes damage to organs.

### **Components:**

#### ***Trade Secret Molybdenum Compound:***

Assessment: May cause respiratory irritation.

### **STOT Specific Target Organ Toxicity - repeated exposure**

Causes damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

Not classified based on available information.

According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>LA LMM-6012</b>		<b>GSLA_LMM-6012 Black ScreenPrintable 500g</b>	
Product specification	RS_FP_305653	Revision Date	02/20/2020
Version	2.3	Print Date	02/26/2020
Material number	1407094	Page	Page 10 of 14

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Product:

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

#### Components:

##### **Trade Secret Molybdenum Compound:**

Toxicity to fish : (Oncorhynchus mykiss (rainbow trout)): 100 mg/l  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

(Pimephales promelas (fathead minnow)): 370 mg/l  
Exposure time: 96 h  
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : (Daphnia magna (Water flea)): 100 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202  
Remarks: No toxicity at the limit of solubility

(Daphnia magna (Water flea)): 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
Remarks: No toxicity at the limit of solubility

##### **2-(2-butoxyethoxy)ethanol:**

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 1,300 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae : EC50 (algae): > 100 mg/l  
Exposure time: 96 h

### Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

#### Components:

##### **Trade Secret Molybdenum Compound:**

Biodegradability : Remarks: No data available

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>LA LMM-6012</b>		<b>GSLA_LMM-6012 Black ScreenPrintable 500g</b>	
Product specification	RS_FP_305653	Revision Date	02/20/2020
Version	2.3	Print Date	02/26/2020
Material number	1407094	Page	Page 11 of 14

***2-(2-butoxyethoxy)ethanol:***

Biodegradability : Remarks: No data available

***Trade Secret Silicated compound:***

Biodegradability : Remarks: No data available

***Trade Secret Vanadium Compound:***

Biodegradability : Remarks: No data available

## Bioaccumulative potential

**Product:**

Bioaccumulation : Remarks: No data available

**Components:**

***Trade Secret Molybdenum Compound:***

Bioaccumulation : Remarks: No data available

***2-(2-butoxyethoxy)ethanol:***

Bioaccumulation : Remarks: No data available

Partition coefficient: n-  
octanol/water : log Pow: 0.56 (20 °C)

***Trade Secret Silicated compound:***

Bioaccumulation : Remarks: No data available

***Trade Secret Vanadium Compound:***

Bioaccumulation : Remarks: No data available

## Mobility in soil

**Product:**

Distribution among  
environmental compartments : Remarks: No data available

**Components:**

***Trade Secret Molybdenum Compound:***

Distribution among  
environmental compartments : Remarks: No data available

***2-(2-butoxyethoxy)ethanol:***

Distribution among  
environmental compartments : Remarks: No data available

***Trade Secret Silicated compound:***

Distribution among  
environmental compartments : Remarks: No data available

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>LA LMM-6012</b>		<b>GSLA_LMM-6012 Black ScreenPrintable 500g</b>	
Product specification	<b>RS_FP_305653</b>	Revision Date	<b>02/20/2020</b>
Version	<b>2.3</b>	Print Date	<b>02/26/2020</b>
Material number	<b>1407094</b>	Page	Page 12 of 14

**Trade Secret Vanadium Compound:**

Distribution among environmental compartments : Remarks: No data available

**Other adverse effects**

**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

---

## SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

Waste from residues : Dispose of wastes in an approved waste disposal facility.

---

## SECTION 14. TRANSPORT INFORMATION

**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations**

**49 CFR**

Not regulated as a dangerous good

---

## SECTION 15. REGULATORY INFORMATION

**TSCA list** : TSCA\_12b - Not relevant

**TSCA list** : TSCA 5a - Not relevant

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**CERCLA Reportable Quantity**

# SAFETY DATA SHEET

According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>LA LMM-6012</b>		<b>GSLA_LMM-6012 Black ScreenPrintable 500g</b>	
Product specification	<b>RS_FP_305653</b>	Revision Date	<b>02/20/2020</b>
Version	<b>2.3</b>	Print Date	<b>02/26/2020</b>
Material number	<b>1407094</b>	Page	Page 13 of 14

This material does not contain any components with a CERCLA RQ.

### **SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Acute Health Hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This product contains components that are reportable under the regulation.

Molybdenum trioxide

Certain Glycol Ethers

Vanadium compounds

### **Clean Air Act**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product contains components that are reportable under the regulation.

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product contains components that are reportable under the regulation.

### **Clean Water Act**

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

### **Massachusetts Right To Know**

This product contains components that are reportable under the regulation.

### **Pennsylvania Right To Know**

This product contains components that are reportable under the regulation.

### **New Jersey Right To Know**

This product contains components that are reportable under the regulation.

### **California Prop 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

# SAFETY DATA SHEET



According to OSHA Hazard Communication Standard 29CFR 1910.1200 (HCS 2012)

<b>LA LMM-6012</b>		<b>GSLA_LMM-6012 Black ScreenPrintable 500g</b>	
Product specification	<b>RS_FP_305653</b>	Revision Date	<b>02/20/2020</b>
Version	<b>2.3</b>	Print Date	<b>02/26/2020</b>
Material number	<b>1407094</b>	Page	Page 14 of 14

EINECS (European Union)	: On the inventory, or in compliance with the inventory
SWISS (Switzerland)	: On the inventory, or in compliance with the inventory
TSCA (United States)	: On TSCA Inventory
DSL/NDSL (Canada)	: All components of this product are on the Canadian DSL.
AICS (Australia)	: On the inventory, or in compliance with the inventory
NZioC (New Zealand)	: On the inventory, or in compliance with the inventory
ENCS (Japan)	: On the inventory, or in compliance with the inventory
ISHL (Japan)	: Not in compliance with the inventory
KECI (Korea)	: On the inventory, or in compliance with the inventory
PICCS (Philippines)	: On the inventory, or in compliance with the inventory
IECSC (China)	: On the inventory, or in compliance with the inventory
TCSI (Taiwan)	: On the inventory, or in compliance with the inventory
CICR (Turkey)	: On the inventory, or in compliance with the inventory
INSQ (Mexico)	: On the inventory, or in compliance with the inventory

## SECTION 16. OTHER INFORMATION

Revision Date : 02/20/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN