



EV9275-70

## QL2-OW200L System

**Delivers premium quality drinking water for bottleless coolers and drinking fountains**



QL2-OW200L System: EV9275-70

OW200L Replacment Cartridge:  
EV9619-01

### BENEFITS

Provides sparkling, fresh, premium quality drinking water

Everpure's unique filter blend using activated carbon reduces chlorine taste and odor and other offensive contaminants

Reduces lead to below the Federal Action Level of 10 ppb

Effectively reduces Trihalomethanes (TTHMs)

Precoat submicron technology reduces dirt and particles as small as 1/2 micron in size

Reduces possible health contaminants such as asbestos fibers and Cryptosporidium and Giardia cysts

Sanitary cartridge replacement is simple, quick and clean. Internal filter parts are never exposed to handling or contamination

Features quick release head without shut-off

NSF Certified under NSF/ANSI Standards 42 and 53

### INSTALLATION TIPS

Never use saddle valve for connection

Use 3/8" water line

Install vertically with cartridge hanging down

Allow 2-1/2" clearance below the cartridge for easy cartridge replacement

Flush OW200L cartridge by running water through filter for three minutes at full flow

### OPERATION TIPS

Change cartridges on a regular 6 month preventative maintenance program

Change cartridges when capacity is reached or when pressure falls below 10 psi

Service flow rate must not exceed 0.5 gpm

Always flush the filter cartridge at time of installation and cartridge change

### APPLICATION/SIZING

For office water applications

Bottleless water coolers and drinking fountains

Rated Capacity: 480 gallons (1,816 L)

# QL2-OW200L System

## SPECIFICATIONS

### Overall Dimensions:

19"H x 4.25"W x 4"D

Inlet connection: 3/8"

Outlet connection: 3/8"

### Service Flow Rate:

Maximum 0.5 gpm (1.9 Lpm)

Rated Capacity: 480 gallons

### Pressure Requirements:

10 - 125 psi (0.7 – 8.6 bar), non-shock

### Maximum Temperature:

35 - 100°F (2 - 38°C)

No electrical connection required


### Shipping Weight:

4 lbs.

### Operating Weight:

6 lbs.

The contaminants or other substances removed or reduced by this drinking water system are not necessarily in your water. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used with disinfected water that may contain filterable cysts.



## WARRANTY

Everpure water treatment systems (excluding replaceable elements) are covered by a limited warranty against defects in material and workmanship for a period of five years after date of purchase. Everpure replaceable elements (filter cartridges and water treatment cartridges) are covered by a limited warranty against defects in material and workmanship for a period of one year after date of purchase. See printed warranty for details. Everpure will provide a copy of the warranty upon request.



System Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of:

Standard No. 42: Aesthetic Effects  
Chemical Unit  
Taste and Odor Reduction  
Chlorine Reduction  
Mechanical Filtration Unit  
Particulate Reduction, Class I:  
99.9+% reduction of particles  
one-half micron and larger in size  
Standard No. 53: Health Effects  
Chemical Reduction Unit  
Lead Reduction  
TTHM Reduction  
Mechanical Filtration Unit  
Turbidity Reduction  
Cyst Reduction  
Asbestos Reduction



251 Paterson Avenue • East Rutherford, NJ 07073  
1-800-562-8872 • 201-460-8379 • Fax 201-460-7172 • Email: Joel@Bellaqua.net  
[www.BellaquaInc.com](http://www.BellaquaInc.com)