

Pour Point, °C (°F)	ASTM D97	-60 (-76)	-60 (-76)	-55 (-57)	-55 (-67)	-50 (-58)	-50 (-58)	-50 (-58)	-50 (-58)	-50 (-58)	-50 (-58)
Noack , wt%	ASTM D5800	12.8	12.5	11.8	12.2	10.1	9.2	6.8	9.4	9.2	8.8

Test	Method	Typical Results									
		10W-30	10W-40	10W-60	15W-40	15W-50	20W-50	20W-60	Nitro 50	Nitro 60	
SAE Viscosity Grade	SAE J300										
API Gravity	ASTM D 287	36.75	36.35	34.58	34.58	34.58	34.19	34.19	33.61	33.61	
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	0.841	0.843	0.852	0.852	0.852	0.854	0.854	0.857	0.857	
Viscosity @ 40°C, cSt	ASTM D445	71.0	87.30	171.8	87.98	128.6	129.7	182.6	150.8	181.9	
		@ 100°C, cSt	11.9	14.2	24.1	14.61	18.2	18.4	24.0	20.8	24.3
Viscosity Index	ASTM D2270	165	169	172	174	159	160	162	162	165	
Flash Point, °C (°F)	ASTM D92	260 (500)	260 (500)	260 (500)	260 (500)	260 (500)	260 (500)	260 (500)	270 (518)	270 (518)	
Pour Point, °C (°F)	ASTM D97	-45 (-49)	-45 (-49)	-45 (-49)	-45 (-49)	-45 (-49)	-45 (-49)	-45 (-49)	-40 (-40)	-40 (-40)	
Noack, wt%	ASTM D5800	6.2	7.2	6.9	5.8	6.6	6.3	6.2	6.1	5.3	

The above characteristics are average values based on recent production. Minor variations, which do not affect product performance, are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children. Don't pollute. Conserve resources. Return used oil and container to collection centers
Reference SDS Number 1200 database on our website at www.amtecol.com