SUPER LIFE® 5500D-2T FS SNOW
SUPREME FULL SYNTHETIC LOW SMOKE 2-STROKE SNOWMOBILE OIL

SUPER LIFE® 5500D-2T FS SNOW is supreme full synthetic two - stroke motor oil specially formulated from synthetic fluids with advanced performance additives to provide maximum performance, superior cold temperature protection, quick starts in extreme cold, outstanding clean-burning performance while protecting vital system parts in 2 –cycle snowmobile engines with very high speed and heaviest load.

APPLICATIONS:

SUPER LIFE® 5500D-2T FS SNOW is recommended for two - stroke engines having either self-mixing or lube injection lubrication systems and suitable for all two – cycle snowmobile engines like Bombardier (Ski-doo), Arcto (Arctic Cat), Lynx , Polaris, Yamaha, Kawasaki, etc.

SUPER LIFE® 5500D-2T FS SNOW is also suitable for high performance 2-stroke engines in AVTs (All terrain vehicles), lawnmowers, etc.

API TC+

JASO FD ISO-L-EGD

BENEFITS:

- Excellent engine protection, maintains strong capacity, prevents deposits on piston, spark-plug and in chimney pot . High reduction of exhaust smoke emissions . Keeps engine always clean .
- Low ash ,synthetic formulation minimizes plug fouling and pre-ignition.
- Low pour point as well as low temperature fluidity for proper and uninterrupted injection system serviceability in extremely cold temperature conditions ,full exhaust gas catalyst compatibility.
- Provides exceptional lubricity and protection against piston scuffing ,ring sticking and bearing wear, rust and corrosion.
- Helps engine running smoothly, freshly and strongly spurting out . Excellent fuel saving .
- Good dissolving in fuel with ratios as specified by engine manufacturer up to maximum of 100:1 .

TYPICAL CHARACTERISTICS

Test	Method	Typical results
API Gravity	ASTM D287	34.97
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	0.850
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D445	42.0 7.8
Viscosity Index	ASTM D2270	158
Flash Point, °C (°F)	ASTM D92	94 (201)
Pour Point , °C (°F)	ASTM D97	-51 (-60)
Sulfated Ash	ASTM D874	0.11

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:
Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children. Don't pollute. Conserve resources. Return used oil and bottle to collection centers.

Reference MSDS No 12020 database on our website at ***www.amtecol.com***