



DESCRIPTION:

- Heavy bodied, flexible, elastomeric caulk and sealant for filling and patching cracks and voids
- Use on vertical masonry, stucco, and concrete block.
- Provides excellent adhesion, long life, and is resistant to failure by expansion, contraction, or other joint movement.
- Fast drying and may be painted with latex or oil base paints.
- For use on interior or exterior surfaces.

ORDERING:

- Available in 1 Gallon and 1 Quart cans.
- Coverage is between 10 to 20 square feet per gallon, per coat, depending on the type of surface and porosity.

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
1214 TROWEL BRUSH CAULK QT	121404	1Q	760428121441	13" x 9" x 6"	6	90 Cases
1214 TROWEL BRUSH CAULK 1G	121401	1G	760428121410	14" x 14" x 8"	4	54 Cases

STORAGE & HANDLING:

- **CONTAINS SOLVENTS, WHICH CAN CAUSE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.**
- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID: In case of skin contact**, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. **For eye contact**, flush immediately with large amounts of water, for at least 15 minutes. **If swallowed**, get medical attention immediately. **If inhalation causes physical discomfort**, move to fresh air. **If discomfort persists** or any breathing difficulty occurs, get medical help.

PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.**
- **Warning! Irritant!** Harmful if swallowed, when tinted, contains ethylene glycol which can cause severe kidney damage when ingested and has been shown to cause birth defects in laboratory animals.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.



WARNING: This product can expose you to chemicals including Titanium Dioxide and Dibutyl Phthalate, which is known to the State of California to cause cancer and reproductive harm. For more information go to www.P65Warnings.ca.gov

1214 WHITE TEXTURED TROWEL GRADE, CAULK & SEALANT

PROPERTIES	
Weight per Gallon	12.44 lbs.
Color(s)	White
Gloss	Flat
VOC Content	46.4g/L (.387lbs/gal) (cal.)
Viscosity	53,000 - 57,000 cps w/#7 spindle @10 rpm
Solid Content by Weight	75%
Solid Content by Volume	54%
Resin	Acrylic
Dry Time @ 77°F & 50% RH Drying times are influenced by ambient temperature and relative humidity.	To Touch: 1-2 Hours

DISPOSAL:

- Contains Organic Solvents which may cause adverse effects to the environment if disposed of improperly.
- Place opened, empty containers in normal refuse for disposal.
- Contact your sanitation department or household hazardous waste coordinator for information concerning re-use, recycling or disposal of solvent-borne paint.
- EAD-C3

CLEANUP:

- Clean hands and tools immediately with warm, soapy water. Clean spills right away with a damp cloth.

DIRECTIONS FOR USE AND SURFACE PREPARATION

- Surface must be free of dirt, oil, grease, efflorescence, chalk, mildew, and loose material.
- Any residual chalk left after pressure washing should be sealed with Anvil #230 or #231 Chalky surface conditioner.
- Joint dimensions not to exceed 1/4" x 1/2" deep. Use polyethylene backing rod for depths exceeding 1/2", especially after routing out masonry joints to remove weakened material.

APPLICATION

- Use broad knife or trowel.

PREVIOUSLY PAINTED SURFACES:

- Wash to remove contaminants.
- Rinse thoroughly with water and allow to dry.
- Remove mildew by washing with a solution of 16 oz (473 mL) liquid household bleach and 2 oz (59 mL) non-ammoniated liquid detergent per gallon (3.785 L) of water.
- Rinse thoroughly with water and let dry for 24 hours before staining.
- Dull glossy areas by light sanding.
- Remove sanding dust.
- Remove loose paint.