



### DESCRIPTION:

- A waterborne acrylic non-cementitious coating that provides an abrasive texture on surfaces where increased traction is required.
- Unique color adaptation properties perfectly complement, Anvil Acrylic Concrete Coatings by providing decorative color match for high traction areas.
- It is non-flammable, low odor and is environmentally safe.
- Can be used as a decorative and protective coating on concrete, asphalt, wood, steel on high traction areas such as steps, floors, pool decks, patios, loading docks, sidewalks, residential garages, carports, inclined residential driveways, ramps, balconies etc.
- Will help prevent weather deterioration of concrete while forming a unique surface texture.
- Decorative color choices are limitless with the addition of Anvil Concrete Stain #1500 or a high quality exterior latex enamel, Gorilla Grip becomes the color of the paint added.

### ORDERING:

- Available in 10 and 40 lb. kits.
- Coverage is approximately 150 square feet for 10 lb kit and 600 square feet for the 40 lb kit

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
2510 GORILLA GRIP STND 10# KIT	251010	2G	760428251025	10" x 10" x 10"	1	36 Cases
2540 GORILLA GRIP STND 40# KIT	254040	5G	760428254057	12" x 12" x 15"	1	36 Cases

### STORAGE & HANDLING:

- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID: In case of skin contact**, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. **For eye contact**, flush immediately with large amounts of water, for at least 15 minutes. **If swallowed**, get medical attention immediately. **If inhalation causes physical discomfort**, move to fresh air. **If discomfort persists** or any breathing difficulty occurs, get medical help.

### PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).**
- **Warning! Irritant!** Harmful if swallowed, when tinted, contains ethylene glycol which can cause severe kidney damage when ingested and has been shown to cause birth defects in laboratory animals.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.



**WARNING:** This product can expose you to chemicals including Crystalline Silica Quartz, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

# 2510 & 2540 GORILLA GRIP ANTI SKID FLOOR COATING STANDARD AGGREGATE

PROPERTIES	
Weight per Gallon	TBD
Color(s)	Determined by color of paint added
VOC Content	99.9 Grams per Liter (cal.)
Viscosity	120+ KU @ 75° F
Solid Content by Weight	73.5%
Solid Content by Volume	58.9%
Resin	Acrylic
Flash Point	None
Dry Time @ 70°F & 50% RH Drying times are influenced by ambient temperature and relative humidity.	To Touch: 1 to 2 Hours To Recoat: 3 to 4 Hours Foot Traffic: 24 Hours Vehicle Traffic: 72 Hours

## MIXING

- Requires the addition of a colored paint to complete the chemical properties of Gorilla Grip.
- We recommend using Anvil Acrylic Concrete Floor & Driveway Water reducible Acrylic Coating #1500.
- Also acceptable are topline exterior gloss/semi-gloss enamels, industrial acrylic enamels or acrylic floor enamels.
- Simply mix 1 quart of enamel to this 10-pound pail, using a mechanical mixer or shaker.
- The color of paint will determine the color of Gorilla Grip.
- DO NOT USE INTERIOR OR FLAT EXTERIOR PAINTS.

## APPLICATION

- Do not dilute, apply if the threat of rain is imminent or if the air/surface temperature is expected to be below 50 degrees F within the first 24 hours of application.
- Coverage is approximately 150 square feet per coat per 10-pound pail (75 sq feet with two coats).
- Apply by roller, brush, texture pump, squeegee or trowel.
- Use a synthetic roller with a short nap (3/16" or shorter) that is designed for the application of adhesives, contact cements, or mastics.
- Two liberal coats are recommended depending on the surface being coated.
- Apply to achieve a uniform textured surface.
- A properly prepared porous surface will allow a film build of 10 MIL wet film thickness, per coat and the desired surface texture.
- Allow two- four hours drying time between coats. If relative humidity is high (80% or higher), allow an extra period of drying time between coats.
- Allow 3 days (72 hours) for a full cure before allowing vehicle traffic on Gorilla Grip. For increased cleanability, and chemical/solvent resistance, top coat with Anvil Acrylic Concrete Floor & Driveway Coating #1500.

## DIRECTIONS FOR USE AND SURFACE PREPARATION

- Remove all dirt, efflorescence, grease, oil, waxes, silicone products and other foreign material that would interfere with the adhesion of the Gorilla Grip.
- Glossy painted surfaces must be de-glossed to allow for better adhesion.
- Clean the de-glossing dust from the surface with a damp cloth before applying Gorilla Grip.
- Patch and repair concrete surfaces with a high quality paintable patch mix.
- Un-coated smooth steel troweled concrete floors (floors with no porosity) must be totally cured, etched, neutralized, rinsed and dried for proper adhesion and durability of Gorilla Grip.
- A properly prepared concrete surface will have the feel of 120 grit sandpaper.
- To further ensure maximum adhesion and durability of Gorilla Grip, concrete should be primed with Anvil GripTite High Adhesion Primer #1750, Bare metal and wood surfaces will require priming with Anvil 1606 Rust Inhibitive Universal Primer.

## CLEANUP:

- Warm water - mild detergent.