



DESCRIPTION:

- Acrylic Latex Siliconized Caulk with excellent adhesion, long life, formulated to last. Multi-purpose adhesive caulk for interior and exterior use.
- Excellent flexibility and resistant to failure by expansion, contraction or other joint movement. Fast drying - repaint with latex or oil paints.
- Safe, latex-based with a water clean-up formula.
- Use on cracks, joints, openings around interior or exterior doors, windows, siding panels, entry pipes, vents, flashing, steps, chimneys, wood, metal, brick, stone, marble, glass or concrete.

ORDERING:

- Available in 11 fl. oz. tubes.

PRODUCT	NO	SIZE	UPC	Case Qty.
1200 ROOF-TEC SILICONIZED CAULK	120009	11 oz	760428120093	30

STORAGE & HANDLING:

- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID: In case of skin contact**, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. **For eye contact**, flush immediately with large amounts of water, for at least 15 minutes. **If swallowed**, get medical attention immediately. **If inhalation causes physical discomfort**, move to fresh air. **If discomfort persists** or any breathing difficulty occurs, get medical help.

PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.**
- **Warning! Irritant!** Harmful if swallowed.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.



WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

1200 ACRYLIC LATEX SILICONIZED CAULK

PROPERTIES	
Color(s)	White
VOC Content	46.4 Grams per Liter (cal.)
Odor	Non-descript
Flash Point	None

DIRECTIONS FOR USE AND SURFACE PREPARATION

- Apply to clean, dry, grease-free surfaces.
- Joint dimensions not to exceed 1/4" x 1/2" deep.
- Use polyethylene backing rod for depths exceeding 1/2", especially after routing out masonry joints to remove weakened material.

APPLICATION

- Use Caulk Gun
- Apply tube bead 1/4" - 3/8" as desired.

CLEANUP:

- Water.