



#### DESCRIPTION:

- Rejuvenates wood and concrete with an eco-friendly textured coating.
- Durable coating formulated for vertical and horizontal surfaces, wood and concrete surfaces.
- Recommended for properly prepared exterior, weathered or cracked wood and composite surfaces such as decks, railings, porches, railings, OR concrete surfaces such as pool decks, patios and walkways.
- Beautiful textured solid color finish offers maximum protection while it repairs structurally sound, wooden and composite decks, concrete patios, walkways steps, preserving the surface for years.
- Encapsulates splinters and fills cracks, creating a beautiful slip resistant finish that is scuff, peel and chip resistant.
- Protects both interior/exterior vertical/horizontal wood and concrete surfaces with lasting durability.

#### ORDERING:

- Available in 1 gallon cans and 5 gallon buckets.
- Coverage Rate: 120-160 sq. feet per coat  
80 sq. ft. in two coats

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
<b>SEE PRODUCT DETAILS ON PAGE 3</b>						

#### STORAGE & HANDLING:

- **CONTAINS SOLVENTS, WHICH CAN CAUSE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.**
- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID:** In case of skin contact, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. For eye contact, flush immediately with large amounts of water, for at least 15 minutes. If swallowed, get medical attention immediately. If inhalation causes physical discomfort, move to fresh air. If discomfort persists or any breathing difficulty occurs, get medical help.

#### PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).**
- **Warning! Irritant!** Harmful if swallowed.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.



**WARNING:** This product can expose you to chemicals including Crystalline Silica and Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

# 9500 SERIES DECK-A-NEW TEXTURED WOOD AND CONCRETE COATING

PROPERTIES	
Weight per Gallon	13.12 lbs.
Color(s)	See chart below
Gloss	Flat
VOC Content	48 Grams per Liter (cal.)
Viscosity	135 KU @ 75° F
Solid Content by Weight	60.0%
Solid Content by Volume	40.95%
Resin	Acrylic
Flash Point	None
Dry Time @ 75°F & 50% RH Drying times are influenced by ambient temperature and relative humidity.	To Touch: 1 to 4 Hours To Recoat: 4 to 6 Hours Foot Traffic: 12 Hours Vehicle Traffic: 3 to 5 days Parked Vehicles: 14 days

## COLORS:

Driftwood 9560	Butternut 9561	Cedar 9562	Walnut 9563
Redwood 9564	White Tint Base 9520	Intermediate Tint Base 9521	Accent Tint Base 9522

## CONCRETE SURFACES

- Remove all dirt, efflorescence, grease, oil, waxes, silicone products, and other foreign material that would interfere with the adhesion of Deck-A-New. Glossy painted surfaces must be de-glossed to allow for better adhesion. Clean the de-glossing dust from the surface with a damp cloth. Patch and repair concrete surfaces with a high-quality patch mix, which is labeled paintable.
- Uncoated smooth, steel-toweled concrete floors (floors with no porosity) must be totally cured, and cleaned with Anvil Clean & Etch #1450. To further ensure maximum adhesion and durability, concrete should be primed with Anvil Bonding Primer AquaSeal #235.

## APPLICATION:

- Apply two coats by brush or roller for best results.
- For normal aged wood, composite or concrete decks use a synthetic roller with a 3/8" nap.
- For extremely weathered, cracked and damaged wood decks, apply with a nylon-loop textured roller. Apply product at a rate of 120 to 160 sq. ft. per gallon, depending on porosity (60-80 sq. ft. in two coats).
- Work in areas of 8' x 10' floor surface. Evenly distribute by roller, working in a slow back and forth motion.
- Finish by lightly rolling in one direction. Apply the second coat right angles to the first coat. If relative humidity is high (80% or higher), allow extra drying time between coats.
- Do not dilute.
- Do not apply if threat of rain is imminent or if the air/surface temperature is expected to be below 50° F within the first 24 hours of application.
- Drying time is 4 hours before the second coat is applied, 24 hours for light foot traffic, 3-5 days for vehicular traffic. Allow 14 days for a full cure before allowing vehicles to park on Deck-A-New.
- For increased cleanability and chemical/solvent resistance with a satin finish, apply a top coat with two coats of Anvil "Wet Look" Super Clear Sealer #2350.

## CLEANUP:

Clean roller covers with soap and water. Dried Deck-A-New will be difficult to remove from any surface.

**DISPOSAL:** Contact your local environmental regulatory agency for procedures of unused product.

## DIRECTIONS FOR USE AND SURFACE PREPARATION:


### WOODEN SURFACES

- Replace rotting or unstable decking boards and remove all loose splinters.
- Clean the surface to remove mildew, dirt, and oil prior to application.
- Patch cracks larger than 1/4" with Anvil Textured Knife Grade Elastomeric Caulking #1214. Level all nail or screw heads.
- It is highly recommended** to use a bonding primer like Anvil Aqua Seal #235 prior to application, especially for extremely weather damaged wood.


# 9500 SERIES DECK-A-NEW TEXTURED WOOD AND CONCRETE COATING

## FOR BEST RESULTS:

## PARA MEJORES RESULTADOS:




Clean Surface Before Use  
Se debe limpiar la superficie antes del uso



Fill Cracks That are Larger Than 1/4 inch  
Rellena grietas de hasta 1/4"

**IT IS HIGHLY RECOMMENDED**  
to use a bonding primer like **Anvil AQUA SEAL #235** prior to application.  
SE RECOMIENDA utilizar una imprimación AQUA SEAL #235 antes de la aplicación.



Apply 2 Coats at Right Angles  
Se debe limpiar la superficie antes del uso



Clean with Soap and Water  
Limpieza con Agua y Jabón

PRODUCT	NO	SIZE	UPC	Case Size (L x W x H)	Case Qty.	Pallet Qty.
9520 DECK-A-NEW WHITE TB 1G	95201	1G	760428952014	14" x 14" x 8"	4	54 Cases
9520 DECK-A-NEW WHITE TB 5G	95205	5G	760428952052	12" x 12" x 15"	1	36 Cases
9521 DECK-A-NEW INTER TB 1G	95211	1G	760428952113	14" x 14" x 8"	4	54 Cases
9521 DECK-A-NEW INTER TB 5G	95215	5G	760428952151	12" x 12" x 15"	1	36 Cases
9522 DECK-A-NEW ACCNT TB 1G	95221	1G	760428952212	14" x 14" x 8"	4	54 Cases
9522 DECK-A-NEW ACCENT TB 5G	95225	5G	760428952250	12" x 12" x 15"	1	36 Cases
9560 DECK-A-NEW DRIFT WOOD 1G	95601	1G	760428956012	14" x 14" x 8"	4	54 Cases
9560 DECK-A-NEW DRIFT WOOD 5G	95605	5G	760428956050	12" x 12" x 15"	1	36 Cases
9561 DECK-A-NEW BUTTERNUT 1G	95611	1G	760428956111	14" x 14" x 8"	4	54 Cases
9561 DECK-A-NEW BUTTERNUT 5G	95615	5G	760428956159	12" x 12" x 15"	1	36 Cases
9562 DECK-A-NEW CEDAR 1G	95621	1G	760428956210	14" x 14" x 8"	4	54 Cases
9562 DECK-A-NEW CEDAR 5G	95625	5G	760428956258	12" x 12" x 15"	1	36 Cases
9563 DECK-A-NEW WALNUT 1G	95631	1G	760428956319	14" x 14" x 8"	4	54 Cases
9563 DECK-A-NEW WALNUT 5G	95635	5G	760428956357	12" x 12" x 15"	1	36 Cases
9564 DECK-A-NEW REDWOOD 1G	95641	1G	760428956418	14" x 14" x 8"	4	54 Cases
9564 DECK-A-NEW REDWOOD 5G	95645	5G	760428956456	12" x 12" x 15"	1	36 Cases