



### DESCRIPTION:

- A heavy bodied, flexible, elastomeric patching material for filling and patching cracks joints and seams on; masonry, stucco, concrete block and metal prior to applying finish.
- Provides excellent adhesion, long life, and is resistant to failure by expansion, contraction, or other joint movement.
- Fast drying and may be painted with latex or oil base paints. For use on interior or exterior surfaces.

### ORDERING:

- Available in Quart cans, 1 Gal. cans, and 5 Gal. buckets.
- Coverage is between 10 to 20 square feet per gallon, per coat, depending on the type of surface and porosity.

| PRODUCT                | NO     | SIZE | UPC          | Case Size (L x W x H) | Case Qty. | Pallet Qty. |
|------------------------|--------|------|--------------|-----------------------|-----------|-------------|
| 1215 TX BRUSH CAULK QT | 121504 | 1Q   | 760428121540 | 13" x 9" x 6"         | 6         | 90 Cases    |
| 1215 TX BRUSH CAULK 1G | 121501 | 1G   | 760428121519 | 14" x 14" x 8"        | 4         | 54 Cases    |
| 1215 TX BRUSH CAULK 5G | 121505 | 5G   | 760428121557 | 12" x 12" x 15"       | 1         | 36 Cases    |

### STORAGE & HANDLING:

- **CONTAINS SOLVENTS, WHICH CAN CAUSE PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.**
- **Warning!** If you scrape, sand, or remove old paint, you may release lead dust. Lead is toxic. Exposure to lead dust can cause serious illness, such as brain damage. Especially in children. Pregnant women should also avoid exposure. Wear an NIOSH-approved respirator to control lead exposure.
- To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying.
- If you experience eye watering, headaches or dizziness, increase fresh air.
- A dust mask does not provide protection against vapors.
- Use only with adequate ventilation.
- Wash thoroughly after handling.
- Clean up carefully with a HEPA vacuum and a wet mop.
- **KEEP AWAY FROM CHILDREN.**
- **KEEP FROM FREEZING**
- **FIRST AID: In case of skin contact**, wash thoroughly with soap and water. If any product remains, gently rub petroleum jelly, vegetable or mineral/baby oil onto skin, then wash again with soap and water. Repeated applications may be needed. Remove contaminated clothing. **For eye contact**, flush immediately with large amounts of water, for at least 15 minutes. **If swallowed**, get medical attention immediately. **If inhalation causes physical discomfort**, move to fresh air. **If discomfort persists** or any breathing difficulty occurs, get medical help.

### PRECAUTIONS:

- Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).**
- **Warning! Irritant!** Harmful if swallowed, when tinted, contains ethylene glycol which can cause severe kidney damage when ingested and has been shown to cause birth defects in laboratory animals.
- Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- May cause eye, nose and throat irritation.
- Do not take internally.
- Do not breathe vapors or spray mist.
- Avoid contact with skin and eyes. Wear eye protection and protective clothing.
- **For emergency information call (800) 545-2643.**
- For additional safety information, refer to the Safety Data Sheet for this product.
- If properly used, a respirator may offer additional protection. Obtain professional advice before using.
- Close container after each use.



**WARNING:** This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

# 1215 ROOF-TEC ELASTOMERIC BRUSH GRADE, CAULK & SEALANT

| <b>PROPERTIES</b>   |   |
|---|---|
| Weight per Gallon   | 9.9 lbs.  |
| Color(s)  | White   |
| Gloss   | Flat  |
| VOC Content   | 88.5 Grams per Liter (cal.)   |
| Viscosity   | Mastic-like   |
| Solid Content by Weight   | 59.1%   |
| Solid Content by Volume   | 51.4%   |
| Resin   | Acrylic Latex   |
| Dry Time @ 70°F & 50% RH<br>Drying times are influenced by ambient temperature and relative humidity. | To Touch: 1 Hour<br>To Recoat: 2 to 4 Hours<br>Full Cure: (1/8" thick single coat) 24 Hours |

- Contains Organic Solvents which may cause adverse effects to the environment if disposed of improperly.
- Place opened, empty containers in normal refuse for disposal.
- Contact your sanitation department or household hazardous waste coordinator for information concerning re-use, recycling or disposal of solvent-borne paint.

## **CLEANUP:**

- Clean up with warm, soapy water.

## **DIRECTIONS FOR USE AND SURFACE PREPARATION**

- Surface must be free of dirt, oil, grease, efflorescence, chalk, mildew, and loose material.
- Any residual chalk left after pressure washing should be sealed with Anvil #230 or #231 Chalky surface conditioner.
- New Galvanized metal should be treated to remove mill oils.
- Ferrous metal should be free from rust and primed with Anvil 1606 Rust Inhibitive Universal Primer.

## **APPLICATION**

- Apply with brush or roller.
- Build up area by layering application.
- Allow to dry thoroughly before applying a new layer.
- Fiberglass mesh may be used between layers to bridge seam or crack.
- Do not apply below 50° F.
- Do not apply when rain, cold or nightfall is imminent.

## **TINTING:**

- Not Recommended.

## **DISPOSAL:**