



DURALIFE® 3000 STOU **SUPER TRACTOR OIL UNIVERSAL LUBRICANT**

DURALIFE® 3000 STOU (SUPER TRACTOR OIL UNIVERSAL LUBRICANT) is a super high performance, multifunctional lubricant designed for use in a wide variety of modern farm equipment. It may also be used in applications calling for a “ Universal Tractor Transmission Oil” (UTTO). This product provides excellent performance in diesel/gasoline engines, conventional gear drives, powershift transmissions, hydrostatic transmissions, hydraulics, final drives, power steering systems and oil-immersed brakes operating in agricultural services.

Suitable for manual transmissions and gear-hydraulic-systems in agricultural or construction machinery with HD engine oil of type SAE 15W-40 or SAE 20W-40 or SAE 25W-40. Manual transmissions having API GL4 service recommendation are also serviceable with DURALIFE® 3000 STOU

APPLICATIONS:

- + John Deere JDM J20C, J27
- + Ford ESN-M2C134-D/41B/48C3/86B/159-B/159-C/121-D
- + FNHA-2-C-201.00/ 200.00
- + Case New Holland CNH MAT 3525/3526/3505/3509
- + Case MS 1207/1209/1210/1230
- + New Holland NH 030C/330G/410B/420A/526C
- + Massey Ferguson CMS M 1145/1144/1143/1141/1139/1135/1127
- + Power shift transmissions specifying Allison C-3/C-4 or Caterpillar TO-2 fluids.
- + ZF TE-ML 06A/06B/06C/06F/06L/07B
- + DIN 51524 part 3 : HVLP (except filterability ISO 13357)
 - Meets API CF-4/CF/CE/SF, SAE 10W-40 , API GL-4, ACEA E3

BENEFITS:

- Excellent anti-wear , rust , corrosion protection and anti-foaming characterizes.
- Maintains size , hardness and strength of seals and gaskets.
- Good shear stability , filterability and oxidative stability.
- Excellent low temperature pumpability and performance.

TYPICAL CHARACTERISTICS

Test	Method	Typical results			
		10W-30	10W40	15W-30	15W-40
SAE Viscosity grade	SAE J300	10W-30	10W40	15W-30	15W-40
API Gravity	ASTM D287	30.58	30.03	30.77	29.66
Specific gravity @ 15.6 °C (60°F) , g/l	ASTMD1298	0.873	0.876	0.872	0.878

Viscosity @ 40°C ,cSt @ 100°C , cSt	ASTMD445	62.00 9.82	108.25 15.00	80.00 11.00	106.00 14.20
Viscosity Index	ASTMD2270	142	145	126	136
Flash Point, °C (°F)	ASTMD92	210 (410)	210 (410)	220 (428)	225 (437)
Pour Point, °C (°F)	ASTMD97	-36 (-35)	-36 (-35)	-40 (-40)	-36 (-35)

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS Number 12080 database on our website at www.amtecol.com
OR scan the code for a direct link

