DURALIFE® HEAVY DUTY DOT 4 BRAKE FLUID

Duralife® Heavy Duty DOT 4 Brake Fluid is a heavy-duty, non-mineral fluid based on Glycol Ethers. It is specially developed for all conventional drum and disc-brake hydraulic systems and hydraulic clutch-actuation systems that operate over wide temperature and humidity ranges.

APPLICATIONS:
Duralife® Heavy Duty DOT 4 Brake Fluid is recommended for all vehicles and motorcycles. It meets the requirements of Federal Motor Vehicle Safety Standard (FMVSS) No.116, SAE J 1703, Federal Specification VV-B-680C, ISO 4925 and JIS K2233 class 4.

BENEFITS:

- Good lubricating and anti-wear, anti corrosion properties.
- Good braking performance under wide temperature range
- High boiling point ensures absolute safety under high temperature operation, exceeds requirements of modern vehicles.
- Compatible with rubber components thus preventing fluid loss.
- Prevents seal hardening or softening.
- Mixable with other brake fluids of the same specification.

TYPICAL CHARACTERISTICS

Test	Method	Typical results
Equilibrium Boiling point Dry, ºC (ºF) Wet, ºC (ºF)	FM VSS-116	 250 (482) 170 (338)
Specific Gravity @ 20ºC (68ºF)	ASTMD 1298	1.04
Viscosity @ - 40ºC, cSt @ 100ºC, cSt	FM VSS-116	1180 2.5
PH	FM VSS-116	8.0
Flash point ºC, (ºF)	ASTM D92	130(266)
API Gravity	ASTM 287	4.56

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING: Keep out of reach of children and avoid contact with eyes. Do not discharge used brake fluid into drains.

Reference SDS Number 12029 database on our website at www.amtecol.com OR scan the code for a direct link