



SUPER LIFE® 5500-2T FS SNOW **PREMIUM FULL SYNTHETIC LOW SMOKE 2-STROKE** **SNOWMOBILE OIL**

SUPER LIFE® 5500-2T FS SNOW is a premium full synthetic two - stroke motor oil specially formulated from synthetic fluids with advanced performance additives to provide excellent clean-burning performance while protecting vital system parts in 2 –cycle snowmobile engines.

APPLICATIONS:

SUPER LIFE® 5500-2T FS SNOW is recommended for two - stroke engines having either self-mixing or lube injection lubrication systems and suitable for all two – cycle snowmobile engines like Bombardier (Ski-doo) , Arcto (Arctic Cat) , Lynx ,Polaris , Yamaha ,etc.

SUPER LIFE® 5500-2T FS SNOW is also suitable for high performance 2-stroke engines in AVTs (All terrain vehicles), lawnmowers ,etc.

API TC +

JASO FC ISO-L-EGD

Piaggio Hexagon Detergency

BENEFITS:

- Excellent engine protection, maintains strong capacity, prevents deposits on piston, spark-plug and in chimney pot . High reduction of exhaust smoke emissions . Keeps engine always clean .
- Low ash ,synthetic formulation minimizes plug fouling and pre-ignition.
- Low pour point as well as low temperature fluidity for proper and uninterrupted injection system serviceability in extremely cold temperature conditions ,full exhaust gas catalyst compatibility.
- Provides exceptional lubricity and protection against piston scuffing ,ring sticking and bearing wear, rust and corrosion.
- Helps engine running smoothly, freshly and strongly spurting out . Excellent fuel saving .
- Good dissolving in fuel with ratios as specified by engine manufacturer up to maximum of 100:1 .

TYPICAL CHARACTERISTICS

| Test | Method | Typical results |
|--|---------------|------------------------|
| API Gravity | ASTM D287 | 31.14 |
| Specific Gravity @ 15.6°C (60°F) | ASTM D1298 | 0.87 |
| Viscosity @ 40°C, cSt @ 100°C, cSt | ASTM D445 | 60.5 10.62 |
| Viscosity Index | ASTM D2270 | 167 |
| Flash Point, °C (°F) | ASTM D92 | 90 (194) |

| | | |
|----------------------|-----------|-------------|
| Pour Point , °C (°F) | ASTM D97 | -48 (-54.4) |
| Sulfated Ash | ASTM D874 | 0.11 |

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and bottle to collection centers.

Reference SDS No 12020 database on our website at www.amtecol.com OR scan the code for a direct link

