



SUPER LIFE® 2-STROKE ENGINE OIL

SUPER LIFE® 2-STROKE ENGINE OIL is a high quality two stroke engine oil designed for use in small 2-stroke engine – either air or water cooled. It is formulated from high refined base oils with good low ash additives. It is also suitable for use in both pre-mix and oil injection systems.

APPLICATIONS:

SUPER LIFE® 2-STROKE ENGINE OIL is recommended for 2- stroke engines in motorcycles, lawn mowers, motor scooters, snowmobiles, chain saws, portable generators, three-wheeled motor vehicles ,etc.

API TA , TB, TC

BENEFITS:

- Protects against scuffing, ringsticking ,plug fouling and engine seizures
- Minimizes wear , rust and corrosion to bearings, rod ,crankshaft ,piston and rings.
- Helps engine running smoothly, freshly and strongly spurting out . Excellent fuel saving .
- Good dissolving in fuel with ratios from 10:1 up to 100:1 according to the engine manufacturer's recommendations.

TYPICAL CHARACTERISTICS

Test	Method	Typical results
API Gravity	ASTM D287	30.2
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	0.875
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D445	70.7 9.4
Viscosity Index	ASTM D2270	110
Flash Point, °C (°F)	ASTM D92	100 (212)
Pour Point , °C (°F)	ASTM D97	-12 (10)

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and bottle to collection centers

Reference SDS Number 12025 database on our website at www.amtecol.com
OR scan the code for a direct link

