



# DURALIFE® AUTOMATIC TRANSMISSION FLUID DX DX ATF

**Duralife® Automatic transmission fluid DX** is formulated with highly refined base oils and additives for passenger cars and light trucks equipped with automatic transmissions where DEXRON® II D fluids are recommended.

## APPLICATIONS:

**Duralife® Automatic transmission fluid DX** is recommended for filling and topping-up automatic transmission where EP properties meeting Dexron specification are required. It is also suitable for use in lieu of power steering fluid.

## BENEFITS:

- Excellent friction, oxidation and thermal stability and deposit control under high temperature and severe operating conditions.
- Anti-wear properties to reduce wear or scoring of gear, clutch bands and discs.
- Good compatibility with sealed materials.
- Flows easily at low temperatures providing good cold-start shifting.
- Good antifoam properties.

## TYPICAL CHARACTERISTICS

Test	Method	Typical results
API Gravity	ASTM D287	29.29
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	0.88
Viscosity @ 40°C, cSt	ASTM D445	34.98
@ 100°C, cSt		7.30
Viscosity Index	ASTM D2270	180
Flash Point ,COC, °C (°F)	ASTM D92	180 (356)
Pour Point , °C (°F)	ASTM D97	-40 (-40)
Foam test @ 93.5°C, ml	ASTM D892	0/0

*The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.*

**WARNING:**

Continuous contact with used oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

*Reference SDS Number 12047 database on website [www.amtecol.com](http://www.amtecol.com) OR scan the code for a direct link*

