



***SUPER LIFE® 6500M-4T FS SNOW***  
**SUPREME 4 - STROKE FULL SYNTHETIC**  
**SNOWMOBILE OIL**

*SUPER LIFE® 6500M-4T FS Snow* is Sport Synthetic Motor Oil specially developed to ensure outstanding protection for the engine, wet clutch and gearbox used by ATVs , UTVs , Snowmobiles and other power sports equipment . It is formulated with Synthetic base stocks and an unique additive package chosen for exceptional wear protection, sludge and varnish resistance, and thermal stability . It provides outstanding protection for hot-operating engines and quickly starting up in cold-weather.

**APPLICATIONS:**

*SUPER LIFE® 6500M-4T FS Snow Product* is recommended for all types of 4-stroke engines and transmission on 2-stroke or 4-stroke powered applications of manufacturers including Honda, Yamaha, Bombardier/BRP , Polaris , Suzuki , Kawasaki, etc. where SAE 0W-30 , 0W-40, 5W-30, 5W-40 , 10W-30 and 10W-40 oils are specified.

API SM/CF  
 JASO MA/ MA 2

**BENEFITS:**

- Helps engine reach maximum performance and power , acceleration .
- Excellent for use in both hot and cold temperature extremes.
- Contains no friction modifiers .Give excellent protection for transmissions .
- Outstanding wet clutch protection for maximum power transfer and smooth shifting.
- Help reduce foaming and air-entrainment in high speed engines.
- Help engine running smoothly and freshly .
- Excellent fuel saving, lengthen the oil changing intervals , economize everything . Prolongation of engine life .

**TYPICAL CHARACTERISTICS**

Test	Method	Typical Results
SAE Viscosity grade	SAE J300	0W-40
API Gravity	ASTM D287	33.42
Specific gravity @ 15.6°C (60°F)	ASTM D1298	0.858
Viscosity @ 40°C cSt @ 100°C cSt	ASTM D445	81 14.30
Viscosity Index	ASTM D2270	184
Flash Point, °C (°F)	ASTM D92	235(455)

Pour Point, °C (°F)	ASTM D97	-53(-63.4)
Noack , wt%	ASTM D5800	8.0
Total Base Number, mgKOH/g	ASTM D2896	9.5

*The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.*

**WARNING:**

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children. Don't pollute. Conserve resources. Return used oil and bottle to collection centers.

*Reference SDS No 12022 database on our website at [www.amtecol.com](http://www.amtecol.com) OR scan the code for a direct link*

