



DURALIFE® PRE-DILUTED 50/50 EXTENDED LIFE DEX-COOL® ANTIFREEZE/ COOLANT (ORANGE COOLANT 50/50)

Duralife® Pre-diluted 50/50 Extended Life Dex-cool® Antifreeze / Coolant (Orange Coolant 50/50) is an ethylene glycol/water based formulation. It is ready to use without adding water. This product protects all metal surfaces within the cooling system including solder, copper, brass, steel, cast iron, and aluminum. The effectiveness of the coolant is improved by the anti-foam properties which works by preventing air bubbles from forming and interfering with the coolants ability to cool.



APPLICATIONS:

Duralife® Pre-diluted 50/50 Extended Life Dex-cool® Antifreeze / Coolant (Orange Coolant 50/50) is recommended for automotive and truck cooling systems and other industrial machines.

Duralife® Pre-diluted 50/50 Extended Life Dex-cool® Antifreeze / Coolant (Orange Coolant 50/50) provides protection over a temperature range from -37°C (-34°F) to 129°C (265°F).

It meets the following performance requirements:

- ❖ ASTM D3306, D4340, D4656, D 4985, D5345, D6210/11, D7853.
- ❖ SAE J1034, J1941, J814C, J1038
- ❖ GM 6277M / 6043M/1825M /1899M, Chrysler MS 7170/MS 9760/MS 9769 , DDC 93K217/7SE298, Ford ESE-WSS M97B44-A-D / M97B18-C/M97B51-A1, BS6580 (British Standard) , FVV HEFT R443(Germany), Mercedes Benz 7700, Cummins 90T8-4/3666132/CES 14603 , JIS K 2234 (Japan Standard), JASO M325, Freightliner 48-22880 , John Deere JDM H24 , Kenworth R02617079, VW TL774G Mack 01GS17004 , PACCAR ,International , Volvo, TMC RP-329 /RP-338, MILCID A-A 52624-I-IP-II.
- ❖ Mercedes, BMW, Audi, Toyota/Lexus, Nissan/Infiniti, Subaru.

BENEFITS:

- Service interval : 5 years or 150,000 miles for light duty applications and 6 years or 600,000 miles whichever comes first for heavy duty diesel applications with coolant extended added at 300K miles as required.
- Provides excellent protection for both automotive and heavy duty diesel engines.
- Constant cooling through improved heat exchange in the cooling system.
- Prevents foaming and provides protection against rust and corrosion.
- No effects on automotive rubber hoses, gaskets and synthetic parts.
- Low silicate formulation that reduces drop-out and silicate gel formation.

- Improved hard water stability, due to the absence of phosphates.
- Compatibility with most major brands of coolant.
- Storage stable for at least 8 years.

TYPICAL CHARACTERISTICS

Test	Method	Typical results
Color		Orange
PH	ASTM D1287	7.0 – 11.0
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	1.02 – 1.15
Freezing point, °C(°F) max	ASTM D1177	-37 (-34)
Boiling point ,°C(°F) min	ASTM D1120	108 (226)
Water, % wt	ASTM D 1123	50

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING: Corrosion liquid! Harmful if takes internally. Keep out of reach of children and avoid contact with eyes. Do not discharge used liquid into drains.

Reference SDS Number 12028 database on our website at www.amtecol.com OR scan the code for a direct link.

