



SUPER LIFE® 3000-2T

LOW SMOKE 2 STROKE MOTORCYCLE OIL

SUPER LIFE® 3000-2T is a superior quality two stroke engine oil formulated specifically for 2T engine with either self-mixing or lube injection lubrication systems operating under severe conditions or in very strict motor racings .

APPLICATIONS:

SUPER LIFE® 3000-2T is recommended for two stroke engines having either self-mixing or lube injection lubrication systems and suitable for all two stroke motor cycle engines of Europe, Japan, USA : VESPA, PIAGGIO, HONDA, SUZUKI, YAMAHA, KAWASAKI, etc.

API TC

JASO FB

BENEFITS:

- Excellent engine protection, maintains strong capacity, prevents deposits on piston, spark-plug and in chimney pot . High reduction of exhaust smoke emissions . Keeps engine always clean .
- Excellent anti-wear properties, lower corrosion and friction . Prevents engine blocked caused by ring sticking .
- Helps engine running smoothly, freshly and strongly spurting out . Excellent fuel saving .
- Good dissolving in fuel with ratios from 50:1 up to 10:1 (2% to 10%) according to the engine manufacturer's recommendations.

TYPICAL CHARACTERISTICS

Test	Method	Typical results
API Gravity	ASTM D287	29.29
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	0.880
Viscosity @ 40°C, cSt	ASTM D445	70.7
@ 100°C, cSt		9.4
Viscosity Index	ASTM D2270	110
Flash Point, °C (°F)	ASTM D92	100 (212)
Pour Point , °C (°F)	ASTM D97	-15 (5)

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and bottle to collection centers

*Reference SDS Number 12025 database on our website at www.amtecol.com
OR scan the code for a direct link*

