



## DURALIFE® HEAVY DUTY DOT 3 BRAKE FLUID

**Duralife® Heavy Duty DOT 3 Brake Fluid** is a heavy -duty , non-mineral fluid based on Glycol and Glycol Ether fluid. It is specially designed for use in hydraulic brake system(disc and drum brakes) of any commercial vehicles , passenger cars and motorcycles where the manufacturer requires the use of a DOT 3 performance level product.

### APPLICATIONS:

**Duralife® Heavy Duty DOT 3 Brake Fluid** is recommended for all vehicles and motorcycles. It meets the requirements of Federal Motor Vehicle Safety Standard (FMVSS) No.116, SAE J 1703 , Federal Specification W-B-680C.

### BENEFITS:

- Good lubricating and anti-wear, anti corrosion properties.
- Good braking performance under wide temperature range
- High boiling point ensures absolute safety under high temperature operation, exceeds requirements of modern vehicles.
- Compatible with rubber components thus preventing fluid loss.
- Prevents seal hardening or softening.
- Mixable with other brake fluids of the same specification.



### TYPICAL CHARACTERISTICS

Test	Method	Typical results
Equilibrium Boiling point Dry, °C (°F) Wet, °C (°F)	FM VSS-116	232 (450) 140 (284)
Specific Gravity @ 20°C (68°F)	ASTMD 1298	1.06
Viscosity @ - 40°C, cSt @ 100°C, cSt	FM VSS-116	1250 1.85
pH	FM VSS-116	9.5
Flash point °C, (°F)	ASTM D92	130(266)
API Gravity	ASTM 287	2.0

*The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.*

**WARNING:** Keep out of reach of children and avoid contact with eyes. Do not discharge used brake fluid into drains.

Reference SDS Number 12029 database on our website at [www.amtecol.com](http://www.amtecol.com) OR scan the code for a direct link

