



DURALIFE® FULL SYNTHETIC AUTOMATIC TRANSMISSION FLUID MB 236.15 (ATF- FS MB 236.15)

Duralife® Full Synthetic Automatic transmission fluid MB 236.15 (ATF-FS MB 236.15) is a Premium high-tech energy-saving synthetic automatic transmission fluid for all latest generation Mercedes-Benz Vehicles and AMG models with 7-speed NAG II FE+ automatic transmissions and latest sport car transmissions .

The product can not be used in the previous 5 - and 7- speed transmission cars Mercedes-Benz, which require the ATF tolerances MB (263.10, 236.12 and 236.14) .

APPLICATIONS:

Duralife® Full Synthetic Automatic transmission fluid MB 236.15 (ATF-FS MB 236.15)

meets and exceeds the requirements of MB 236.15

+ Mercedes-Benz 7-G Tronic Plus (NAG II+)

+ MB 001 989 77 03 / 001 989 78 03

BENEFITS:

- Optimizes shifting performance of Mercedes-Benz automatic transmissions.
- Provides impressive fuel economy potential and low-temperature behaviour.
- Excellent friction, oxidation and thermal stability and deposit control under very high temperature and severe operating conditions.
- Excellent anti-wear, antifoam, antirust, anticorrosion properties.
- Good compatibility with seal materials.
- Good balanced coefficient of friction.
- Lowest evaporation losses.
- Flows easily at low temperatures providing good cold-start shifting. Better cold temperature flow properties than conventional ATF.
- A neutral behavior because of inhibition against non-ferrous metals.
- Protects automatic transmission hardware.
- Provides anti-shudder performance and then avoids vibrations on engine fly wheel.
- Assures long equipment life.

TYPICAL CHARACTERISTICS

Test	Method	Typical results
API Gravity	ASTM D287	36.75
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	0.841
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D445	18.50 4.40
Viscosity Index	ASTM D2270	155
Brookfield Viscosity @ -40°C, cP	ASTM D2983	2760
Flash Point , °C (°F)	ASTM D92	175 (347)
Pour Point , °C (°F)	ASTM D97	-53 (-63.4)
Foam test @ 93.5°C, ml	ASTM D892	0/0

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS Number 12091 database on our website at www.amtecol.com OR scan the code for a direct link

