



DURALIFE® FULL SYNTHETIC AUTOMATIC TRANSMISSION FLUID 6HP (6 HP Fluid)

Duralife® Full Synthetic Automatic transmission fluid 6 HP (6HP Fluid) is designed with PAO Synthetic base oils and the latest additive technology for all 6-motion automatic transmissions. This superior Automatic transmission fluid provides better heat resistance, cold flow capabilities and transmission sputter resistance than conventional automatic transmission fluids.

APPLICATIONS:

Duralife® Full Synthetic Automatic transmission fluid 6 HP (6HP Fluid) is a multi-functional fluid that meets or exceeds the following Manufacturer's performance requirements.

- + ZF 6HP19, 6HP21, 6HP26, 6HP28, 6HP32, 6HP34, all ZF4 & 5HP-series Transmissions.
- + ZF Lifeguard 6
- + Audi/VW G 052 162, G 052 025, G 052 990, G 055 025, G 055 005 A1/A2/A6
- + Jaguar C 2 C 8432
- + Porsche P/N 000 043 304 00
- + Land Rover TYK 50 0050, ATF M-1375.4
- + Volvo 97340/97341
- + Shell 134, 3353, LA 2634, M 1375.4
- + BMW LT 71141, LA 2634 Fluids, 7045E, BMW 83220144137/ 83220142516

BENEFITS:

- Excellent friction, oxidation and thermal stability and deposit control under very high temperature and severe operating conditions.
- Excellent anti-wear, antifoam, antirust, anticorrosion properties.
- Good compatibility with seal materials.
- Good balanced coefficient of friction.
- Lowest evaporation losses.
- Flows easily at low temperatures providing good cold-start shifting. Better cold temperature flow properties than conventional ATF.
- A neutral behavior because of inhibition against non-ferrous metals.
- Protects automatic transmission hardware.
- Assures long equipment life.

TYPICAL CHARACTERISTICS

Test	Method	Typical results
API Gravity	ASTM D287	34.97
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	0.85
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D445	27.80 6.20
Viscosity Index	ASTM D2270	183
Brookfield Viscosity @ -40°C, cP	ASTM D2983	4220
Flash Point , °C (°F)	ASTM D92	210 (410)
Pour Point , °C (°F)	ASTM D97	-52 (-61.6)
Foam test @ 93.5°C, ml	ASTM D892	0/0

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS Number 12091 database on our website at www.amtecol.com OR scan the code for a direct link

