



TALON GRIP SLIP RESISTANT ADDITIVE



RESIN: Micronized Polypropylene
COLOR: White Powder Transparent in clear coatings

GLOSS: Semi / Low Luster

DENSITY : 0.90 g/cc

RECOMMENDED ADDITION:

.18lbs. (9102) to a gallon can

.88 lbs. (9105) to a five gallon pail to achieve an increased coefficient of friction for slip resistance.

MEAN PARTICLE SIZE:

160-180 (microns)

50 (mesh)

SOLVENT RESISTANCE:

Can be used in most film forming water-based, solvent-based alkyds, paints, sealers, urethanes and epoxy coatings.

9102

.18 lbs. for 1 gallon

9105

.88 lbs. for 5 gallons



- MICRONIZED POLYMER**
- INCORPORATES EASILY**
- STAYS WELL SUSPENDED**
- GOOD CHEMICAL AND ABRASION RESISTANCE**
- DOES NOT INCREASE VISCOSITY**
- SPHERICAL-SHAPED PARTICLES**
- COMFORTABLE TO BARE FEET AROUND THE POOL**
- ADD TO PAINTS, STAINS AND SEALERS**
- DOES NOT CONTAIN SILICA**

LIMITED WARRANTY AND LIMITATION OF REMEDIES

Anvil Paints & Coatings, Inc., disclaims all expressed warranties except those that appear above. Further, seller disclaims any implied warranty of merchantability of the goods or of the fitness of the goods for any purpose. To the extent allowed by law, any implied warranty of merchantability of fitness applicable Talon Grip is limited to the five (5) year duration of the express warranty and is subject to all the terms and conditions of this limited warranty. Purchaser agrees that in no case shall Anvil Paints & Coatings, Inc. be liable for labor, incidental or consequential damages based upon any legal theory including, but not limited to, damages for loss of profits and/or damage to property or failure due to structural defects, acts of God or causes beyond our control, including the negligence of any person, and any other abuse or misuse of this product by purchaser.

5-YEAR WARRANTY

This product is manufactured to rigid quality control specifications. Anvil Paints & Coatings, Inc. warrants to the original purchaser only, that Talon Grip will be free of manufacturing defects for 5 years from date of purchase when applied in three coats, according to instructions as indicated. If purchaser discovers that Talon Grip has not performed as stated, promptly send written notification of this fact, along with proof of purchase, to Anvil Paints & Coatings, Inc., 1255 Starkey Road, Largo, FL 33771. If Anvil product is found to be defective, Anvil will provide the original purchaser with replacement Talon Grip sufficient to repair the affected area. This remedy is the purchaser's exclusive remedy.

USES, FEATURES & BENEFITS

Anvil Talon Grip Slip Resistant Additive is a finely ground polymer material to be added to paint or stains to achieve a slip resistant surface on walkways, driveways, garage floors, patios, pool decks and other surfaces. It may also be added to paints to create a fine texture effect. The physical properties of Talon Grip's particle size will provide optimum abrasion resistance and is more comfortable to bare feet on pool decks and similar surfaces than sand additives. Talon Grip's low density and insolubility characteristics will reduce or eliminate settling and provide optimum performance in film forming water based or solvent based paints, stains and sealers without changing the viscosity.

TALON GRIP MIXING

Anvil Talon Grip Slip Resistant Additive is designed to be incorporated into a suitable paint or stain. Minimum inclusion ratio of Talon Grip is as follows; 9102 .18 lbs size to a gallon can or 9105 .88 lbs. size to a five-gallon pail. More Talon Grip can be added depending on the desired texturing effect, but not to exceed 8 oz. per gallon. While continually stirring, add Talon Grip to the container of paint, stain or sealer. Talon Grip may tend to float at first but once wet will mix easily. Occasional stirring, during application, may be required in

thinner products to keep the particles well suspended within the coating. Not for use in wood stains. It is recommended that when mixing Talon Grip into unfamiliar coatings, that a small test batch and application be made. Follow application instructions of the paint, stain or sealer.

CAUTION

Talon Grip Slip Resistant Additive is not hazardous and does not contain silica, but it should be treated as a nuisance dust while incorporating it into its intended vehicle. Use with adequate ventilation. Use appropriate, properly fitted respirator protection filter apparatus and avoid breathing dust and particles. If dizziness, headache or eye watering occurs, get to fresh air, leave the area. In case of eye contact, flush with large amounts of water for at least 15 minutes. Get medical attention if irritation persists.

LIMITATIONS

Talon Grip Slip Resistant Additive will increase the texturing effect of a paint, stain or clear coating, but the coating that Talon Grip is added to should not be considered Non-Skid or Anti-Skid. For a more abrasive floor coating where increased traction is required, consider using Anvil Gorilla Grip Anti Skid Floor Coating.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE. ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the **National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.**

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED, WHEN TINTED, CONTAINS ETHYLENE GLYCOL WHICH CAN CAUSE SEVERE KIDNEY DAMAGE WHEN INGESTED AND HAS BEEN SHOWN TO CAUSE BIRTH DEFECTS IN LABORATORY ANIMALS. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION.

To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use.

FIRST AID: if you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

Revised 11/2017 (Supersedes all previous versions)

Manufactured with Pride by **Anvil Paints & Coatings, Inc.** • 1255 Starkey Road • Largo, FL 33771 • **1-800-822-6776** • www.anvilpaints.com

© All rights reserved. 10/2017