



SUPER LIFE® 8000 **SYNTHETIC BLEND MOTOR OILS**

SUPER LIFE® 8000 Products are formulated with a mixture of high-tech synthetic and premium quality base stocks and the advanced additive technology to protect the engines during high temperature conditions.

APPLICATIONS:

SUPER LIFE® 8000 Products are recommended for both gasoline and diesel engines in passenger cars, light- trucks, vans including turbocharged engines.

API SL/ SJ : SAE 5W-20, 5W-30, 10W-30, 10W-40, 15W-40, 20W-50

ILSAC GF-3: SAE 5W-20, 5W-30, 10W-30

Energy conserving: SAE 5W-20, 5W-30, 10W-30

BENEFITS:

- Excellent protection against the build up of harmful sludge and wear in hotter running and high RPM or heavy duty operating conditions such as severe stop- and -go driving as well as during low temperature short trip winter driving.
- Protect against rust and corrosion under severe low temperature operating conditions.
- Improve resistance to thermal breakdown.
- Lower volatility to prevent oil from boiling away.
- Easier cold starting.
- Improve fuel efficiency.
- Extend engine life.
- Excellent at maintaining engine cleanliness.

TYPICAL CHARACTERISTICS

Test	Method						
SAE Viscosity grade	SAE J300	5W-20	5W-30	10W-30	10W-40	15W-40	20W-50
API Gravity	ASTM D287	33.23	33.03	30.77	30.21	29.47	28.02
Specific gravity @ 15.6 °C (60°F)	ASTMD1298	0.859	0.860	0.872	0.875	0.879	0.887
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTMD445	46 8.4	65.45 10.98	70.35 10.50	98.10 14.30	105.5 14.00	180.0 19.5
Viscosity Index	ASTMD2270	161	160	135	150	134	124
Flash Point, °C (°F)	ASTMD92	225(437)	225(437)	225(437)	230(446)	232(450)	235(455)
Pour Point, °C (°F)	ASTMD97	-38(-36)	-38(-36)	-38(-36)	-37(-35)	-36(-33)	-26(-15)

The above characteristics are average values based on recent production. Minor variations, which do not affect product performance, are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children. Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS No: 12023 database on our website at www.amtecol.com OR scan the code for a direct link

