



LX™-GC30 Hi-UV Ground Cover Fabric

Carthage Mills LX-GC30 is our premium woven ground cover fabric. LX-GC30 is a woven polypropylene geotextile with colored marker yarns every 12 inches for quick and easy plant alignment and presentation. Puncture and tear resistant, Carthage Mills' LX™-GC30 sustains pedestrian and light vehicle traffic, and is treated with a special UV protection, and is designed to last approximately 10 years in sunlight and indefinitely in the shade. It is resistant to insects and rodents and will not rot or support mildew.

PROPERTY	TEST METHOD	UNITS	TYPICAL VALUES
Weight (Typical)	ASTM D 3776	oz/yd ²	3.0
Grab Tensile Elongation	ASTM D 4632	%	22 x 19
Grab Tensile	ASTM D 4632	lbs	190 x 110
Permittivity	ASTM D 4491	Sec ⁻¹	0.210
Water Flow	ASTM D 4491	gal/min/ft ²	16
UV Resistance	ASTM D 4355	% Retained	80% @ 3500 hours
Marker Yarn Color	---	Color	Green
Call for Roll Sizes			

NOTES: Mullen Burst Strength ASTM D 3786 is no longer recognized by ASTM D35 on Geosynthetics. Puncture Strength ASTM D 4833 is not recognized by AASHTO M 288-15 and has been replaced with CBR Puncture ASTM D 6241.

- Unless otherwise stated, all values stated here are Minimum Average Roll Values (MARV).
- The properties reported above are effective 05-01-19 and are subject to change without notice.

Carthage Mills assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. Carthage Mills disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.