



## REINFORCING SUCCESS

**WINFAB S2** is manufactured using 100% agricultural grade wheat straw that is stitched between 2 layers of polypropylene netting.

**WINFAB S2** is excellent in holding seeds and soil in place while vegetation is developed.



PROPERTY	TEST METHOD	TYPICAL ENGLISH	TYPICAL METRIC
Wide Width Tensile	ASTM D6818	119 x 116 lbs/ft	2.83 x 1.69 kN/m
Mass/Unit Area	ASTM D6475	9.24 oz/yd <sup>2</sup>	313 g/m <sup>2</sup>
Thickness	ASTM D6525	.335 in	8.5 mm
Ground Cover	ASTM D6567	91%	91%
Light Penetration	ASTM D6467	8.3%	8.3%
Water Absorption	ASTM D1117	435%	435%
Stitching	-	2 in centers	5.08 cm centers
Netting	-	3/8 in x 3/8 in	.9525 cm x .9525 cm

PROPERTY	TEST METHOD	TYPICAL ENGLISH	TYPICAL METRIC
Roll Dimensions	Measured	8 ft x 112.5 ft	2.44 x 34.29 m
Roll Area	Measured	100 yd <sup>2</sup>	83.61 m <sup>2</sup>

**Disclaimer:** WINFAB assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. WINFAB disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product. The property values listed above are subject to change without notice.

© 2018 WINFAB