




# PRODUCT DATA SHEET

## WINFAB Type 2

### DOT FTB

**WINFAB Type 2 DOT FTB** is a Yellow PVC coated polyester fabric floating turbidity barrier. It is designed to control silt, floating vegetation, and other debris in ditches, streams, canals, marshes, ponds, and lakes.

**WINFAB Type 2 DOT FTB** can be used in Fresh, Salt, and Brackish water.



PROPERTY	TYPICAL ENGLISH
Fabric Weight	18.0 oz/yd <sup>2</sup>
Fabric Thickness	20 mils
Rope	5/8 in Diameter Poly
Load Cable	5/16 in Galvanized Steel with PVC Coating on top
Grommets	#5 Brass
Chain Ballast	5/16 in Galvanized
Seams	Heat Sealed
EPS Flotation	8 x 8 in
Freshwater Buoyancy	26.7 lbs/ft
Saltwater Buoyancy	28.4 lbs/ft
Height	5 ft (Standard) Custom Available
Length	50 ft (Standard) Custom Available

**Disclaimer:** WINFAB assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. WINFAB disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product. The property values listed above are subject to change without notice.