



SUPER LIFE 5500D-2T FS **SUPREME FULL SYNTHETIC LOW SMOKE 2-STROKE** **MOTORCYCLE OIL**

SUPER LIFE 5500D-2T FS is a supreme full synthetic two - stroke engine oil specially formulated from synthetic oils with advanced additives to provide excellent clean-burning performance while protecting vital system parts.

APPLICATIONS:

SUPER LIFE 5500D-2T FS is recommended for two - stroke engines having either self-mixing or lube injection lubrication systems and suitable for all two - stroke motorcycle engines of Europe, Japan, USA : VESPA, PIAGGIO, HONDA, SUZUKI, YAMAHA, KAWASAKI, etc. JASO FD ISO-L-EGD TISI

BENEFITS:

- Excellent engine protection, maintains strong capacity, prevents deposits on piston, spark-plug and in chimney pot. High reduction of exhaust smoke emissions.
- Provides exceptional lubricity and protection against piston scuffing, ring sticking and bearing wear, rust and corrosion.
- Helps engine running smoothly, freshly and strongly spurting out . Excellent fuel saving .
- Achieves maximum horsepower .
- Good dissolving in fuel with ratios from 50:1 up to 10:1 (2% to 10%) according to the engine manufacturer's recommendations

TYPICAL CHARACTERISTICS

Test	Method	Typical results
API Gravity	ASTM D287	35.75
Specific Gravity @ 15°C (60°F)	ASTM D1298	0.846
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D445	42 7.8
Viscosity Index	ASTM D2270	158
Flash Point, °C (°F)	ASTM D92	102 (216)
Pour Point , °C (°F)	ASTM D97	-45 (-49)

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and bottle to collection centers

*Reference SDS No12020 database on our website at www.amtecol.com
OR scan the code for a direct link*

