

Hunter 300-400 Assembly Instructions

1. Cut all metal bands and zip ties away from the unit
2. Remove the **Wheel Extensions** from under the unit and lay to the side
3. Open the **Versa Seeder Assembly** and locate the plastic bag, bag consist of
 - a. (2) ½” bolts with nylocks (these are for the **Wheel Extensions**)
 - b. (2) ½” bolts with (2) washers each (these are for the **1-Point Hitch Receiver**)
4. Included in the **Versa Seeder** is the power supply and it consist of
 - a. **Control Box** (raises/lowers unit - up/down & activates seeder motor - on/off)
 - b. **Jack Accessory Cable** (connects to cables located on (L) front of Plotmaster)
 - c. **Battery Ring Terminals** (connects to the towing vehicle battery)
5. Once you have located all of the items start by assembling the **Wheel Extensions** first
6. Align the hole in the extension with the hole in the **Axle Tube** and place bolt in hole
 - a. If you do not have clearance, then using the **Control Box** you will toggle the switch
So that the **Axle Tube** rotates and the holes are aligned horizontally
7. Once you have the **Wheel Extensions** on and secured you will raise the unit to gain access to the one **1-Point Hitch Receiver** that mounts to the front of the unit for towing
 - a. While toggling the up/down the front of the unit will raise and clear the pallet
 - b. This happens because the weight of the rear lets the front end rise up.
8. Once you have clearance you will remove the **1-Point Hitch Receiver**
9. Using the (2) ½” bolts with washer, align the **1-Point Hitch Receiver** with the hole on the frame and insert the first bolt (making sure 1 washer is at the head of the bolt and the other is between the frame and the nylock nut)
10. Once you have inserted both ½” bolts w/washers you then need to connect the top link to the **1-Point Hitch** and then back to the frame (pins are already in place, just remove, align top link and re-insert pins with spring clips)
11. Lastly, connect your **Battery Ring Terminals** to the towing vehicle battery, connect the **1-Point Hitch Receiver** to your ball coupler and pull the unit away from the pallet.
 - a. 1-Point Hitch Couple is 2” – Set Standard for 1 7/8” Ball butt fits 2” Ball as well