



## **DURALIFE® SYNTHETIC BLEND EXTREME PRESSURE HEAVY DUTY RED TACKY INDUSTRIAL GEAR OIL SBEPT 220**

**DURALIFE® SYNTHETIC BLEND EXTREME PRESSURE HEAVY DUTY RED TACKY INDUSTRIAL GEAR OIL SBEPT 220** is formulated with a selected blend of PAO synthetic and high quality mineral base oils with Sulfur-phosphorus Extreme pressure additives to give minimum gear wear , maximum load carrying capacity, corrosion protection, and outstanding resistance to high temperature sludging. The tacky agent provides excellent adhesion performance due to the oil always sticks to metal surfaces.

### **APPLICATIONS :**

**DURALIFE® SYNTHETIC BLEND EXTREME PRESSURE HEAVY DUTY RED TACKY INDUSTRIAL GEAR OIL SBEPT 220** is recommended for all types of industrial and mobile equipment requiring EP gear oils such as the enclosed gear drives and speed reducers, ranging from small gearboxes to large , high-power units on metal rolling mills, cement mills , sugar mills, steel mills, quarries, metal process plants, conveyors and mine hoists ,agitators, extruders, pressers, etc., and for a wide of marine applications include marine gearing including main propulsion, centrifuges, deck machinery such as winches, windlasses, cranes, turning gears, pumps, elevators and rudder carries. They are also suitable for chain cases, sprockets, slide guides, flexible couplings, and plain and rolling element bearings operating under severe or shock load conditions.

It is compatible with non-EP copper and its alloys and hence suitable for gearboxes and drives incorporating bronze components, such as worm wheels.

Meets the requirements of:

DIN 51517 Part 3

AGMA 9005 - D94 EP, 9005 – E 02EP

ISO 12925-1 Type CKC/ CKD

US Steel 224

David Brown Type E

Hansen Transmissions

Cincinnati Milacron

Müller Weingarten equipment

### **BENEFITS :**

- Superior antirust , anti-wear and EP properties.
- Excellent adhesion to metal surfaces.
- Extend gear life due to high load carrying and outstanding ability to keep gear surfaces free of deposits.
- Excellent thermal and oxidation stability.
- Non corrosive steel, cast iron , copper ,and bronze.
- Superior demulsibility as it separate from water easily.

### **TYPICAL CHARACTERISTICS :**

<b>Test</b>	<b>Method</b>	<b>SBEPT 220</b>
API Gravity	ASTM D287	24.00
AGMA #		5EP
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	0.910
Viscosity @ 40°C, cSt	ASTM D445	220
Viscosity Index	ASTM D 2270	108
Flash Point, COC, °C (°F)	ASTM D92	240 (464)
Pour Point, °C (°F)	ASTM D97	-25 (-13)
F Z G Gear Test , Fail stage (A/8.3/90)	ISO 14635-1 / DIN 51354	>12
Foam Test Seq 1 , ml	ASTM D 892	0/0
4-Ball EP Test, Load-wear index, kg Weld Point, kgD-2783	ASTM D 2783	47 400
4-Ball Wear Test, 20kg, 1 hr., 1800 rpm, 54°C ,Wear scar diameter, mm	ASTM D 2266	0.4
Timken OK Load, lb	ASTM D 2782	75

*The above characteristics are average values based on recent production .Minor variations which do not affect product performance are to be expected in normal manufacture .*

**WARNING :**

Continuous contact with used oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and bottle to collection centers

Reference SDS No 12140 database on our website at [www.amtecol.com](http://www.amtecol.com)

