

SAFETY DATA SHEET

Page 1 of 6

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MANUFACTURER'S NAME / ADDRESS

ARIZONA POLYMER FLOORING
4565 W. WATKINS ST.
PHOENIX, AZ 85043

TRADE NAME: VAPORSOLVE® TIE COAT PART B
COLOR: CLEAR
MAIN USE: SPECIALTY FLOORING RESIN

EMERGENCY TELEPHONE NUMBER: (800) 424-9300 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

GLOBALLY HARMONIZED SYSTEM (GHS)

CLASSIFICATION:

SKIN CORROSION: CATEGORY 2

EYE DAMAGE: CATEGORY 2A

SKIN SENSITIZATION: SUB-CATEGORY 1

REPRODUCTIVE TOXICITY: CATEGORY 2

GHS LABEL ELEMENTS

HAZARD PICTOGRAMS



SIGNAL WORD: DANGER!

HAZARD STATEMENTS

H315: CAUSES SKIN IRRITATION

H317: MAY CAUSE AN ALLERGIC SKIN REACTION

H319: CAUSES SERIOUS EYE IRRITATION

H361: SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD

H370: CAUSES DAMAGE TO ORGANS (CNS, EYES RESPIRATORY TRACT)

H372: CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE (LUNGS, SKIN)

PRECAUTIONARY STATEMENTS:

PREVENTION

P201: OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.

P202: DO NOT HANDLE UNTIL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD

P261: AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY

P264: WASH SKIN THOROUGHLY AFTER HANDLING

P270: DO NOT EAT, DRINK OR SMOKE WHEN USING THIS PRODUCT

P272: CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE

P273: AVOID RELEASE TO ENVIRONMENT

P280: WEAR PROTECTIVE GLOVES/ PROTECTIVE CLOTHING/ EYE PROTECTION/ FACE PROTECTION

SAFETY DATA SHEET

VAPORSOLVE® TIE COAT PART B

Page 2 of 6

SECTION 2: HAZARDS IDENTIFICATION CON'T.

PRECAUTIONARY STATEMENTS

RESPONSE

P308+P313: IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.

P303+P361+353: **IF ON SKIN (OR HAIR):** REMOVE/TAKE OFF IMMEDIATELY ALL CONTAMINATED CLOTHING. RINSE SKIN WITH WATER/SHOWER

P305+P351+P338: **IF IN EYES:** RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO SO. CONTINUE RINSING.

P304+P340 **IF INHALED:** REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING

P301+P331: IF SWALLOWED: RINSE MOUTH. DO NOT INDUCE VOMITING

P337+P313: IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION

P361+P364: TAKE OFF CONTAMINATED CLOTHING AND WASH BEFORE REUSE

P391: COLLECT SPILLAGE

STORAGE

P405: STORE LOCKED UP

DISPOSAL

P501: DISPOSE OF CONTENTS/CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT

OTHER HAZARDS

NO DATA AVAILABLE

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

<u>HAZARDOUS INGREDIENTS</u>	<u>Wt. %</u>	<u>CAS Number</u>
2-PROPOXYETHANOL	1-5	002807-30-9

SECTION 4: FIRST AID MEASURES

GENERAL: REMOVE PERSON FROM AFFECTED AREA AND MAKE COMFORTABLE. TREAT SYMPTOMATICALLY.

EYES: FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

SKIN: REMOVE PRODUCT AND FLUSH AFFECTED AREA WITH WATER FOR 15 MINUTES. IF IRRITATION PERSISTS GET MEDICAL ATTENTION.

INHALATION: MOVE TO FRESH AIR. GIVE ASSISTED RESPIRATION IF BREATHING HAS STOPPED OR IS LABORED (CALL A PHYSICIAN).

INGESTION: GIVE 3 – 4 GLASSES OF WATER OR MILK IF PERSON CONSCIOUS. **DO NOT INDUCE VOMITING!** OBTAIN MEDICAL CARE AND TREATMENT.

SAFETY DATA SHEET

VAPORSOLVE® TIE COAT PART B

Page 3 of 6

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: NA
CONDITIONS OF FLAMMABILITY: NA
FLAMMABLE LIMITS: LEL: NE UEL: NE
HAZARDOUS COMBUSTION PRODUCTS: CO, CO₂,
EXTINGUISHING MEDIA: WATER, CO₂, DRY CHEMICAL
SPECIAL FIRE FIGHTING PROCEDURES: NONE LIKELY WITH SMALL QUANTITIES. FOR LARGE QUANTITIES, FIREFIGHTERS AND OTHERS EXPOSED TO VAPORS OR PRODUCTS OF COMBUSTION SHOULD WEAR BUTYL RUBBER BOOTS, GLOVES AND BODY SUIT. SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN.
UNUSUAL FIRE AND EXPLOSIVE HAZARDS: POLYMER FILM CAN BURN, MATERIAL CAN SPLATTER ABOVE 100°C

SECTION 6: ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: COVER SPILLS WITH ABSORBENT. PLACE IN METAL CONTAINERS FOR RECOVERY OR DISPOSAL. PREVENT ENTRY INTO SEWERS, STORM DRAINS, AND WATERWAYS.

SECTION 7: HANDLING AND STORAGE

GENERAL: STORE IN COOL, WELL VENTILATED AREAS. KEEP AWAY FROM HEAT AND OPEN FLAMES. AVOID PROLONGED INHALATION OF HEATED VAPORS OR MISTS. AVOID PROLONGED SKIN CONTACT.
STORAGE: STORE BETWEEN 40°F AND 100°F PROTECTED FROM FROST AND DIRECT SUNLIGHT.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

INGREDIENTS (CAS)	<u>EXPOSURE LIMITS (ppm)</u>				OTHER
	OSHA		ACGIH		
	TWA	STEL	TWA	STEL	
002807-30-9	NE	NE	NE	NE	

LEGEND: (M) MAX. EXPOSURE LIMIT; (S) OCCUPATIONAL EXP. LIMIT; (R) SUPPLIERS REC. LIMIT, (+) PERCUTANEOUS RISK
NOTE 1: VALUES MEANINGFUL ONLY WHEN HARDENED PRODUCT IS ABRADED, GROUND, ETC.

ENGINEERING CONTROLS: NO SPECIFIC CONTROLS NEEDED. GENERAL AND LOCAL EXHAUST RECOMMENDED.

RESPIRATORY PROTECTION: NONE REQUIRED IN ADEQUATELY VENTILATED AREAS. IF VAPOR CONCENTRATION EXCEEDS 20ppm FOR LONGER THAN 15 MINUTES, A NIOSH APPROVED RESPIRATOR FOR ORGANIC VAPORS IS RECOMMENDED.

PROTECTIVE GLOVES: NITRILE RUBBER

EYE PROTECTION: SPLASH-PROOF GOGGLES OR CHEMICAL SAFETY GLASSES

OTHER PROTECTIVE EQUIPMENT: LONG SLEEVED SHIRTS AND TROUSERS. EMERGENCY SHOWERS AND EYE WASH STATIONS SHOULD BE READILY ACCESSIBLE.

SAFETY DATA SHEET

VAPORSOLVE® TIE COAT PART B

Page 4 of 6

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: >100°C (>212° F)	SPECIFIC GRAVITY: 1.0-1.1
VAPOR PRESSURE: ND	MELTING POINT: ND
VAPOR DENSITY: >1 (AIR = 1)	EVAPORATION RATE: <1 (BUTYL ACETATE = 1)
SOLUBILITY IN WATER: DILUTABLE	pH: 8.0 TO 11.5
COEFFICIENT of WATER/OIL DISTRIBUTION: ND	ODOR THRESHOLD: ND
APPEARANCE AND ODOR: MILKY WHITE LIQUID, MILD ODOR	
% VOLATILES BY VOLUME: 65%	% SOLIDS BY WEIGHT: 40%

SECTION 10: STABILITY AND REACTIVITY

STABILITY: STABLE

CONDITIONS TO AVOID: AVOID ELEVATED TEMPERATURES

INCOMPATIBILITY (MATERIAL TO AVOID): OXIDIZING AGENTS (PEROXIDES, NITRATES), ACIDS.

HAZARDOUS DECOMPOSITION PRODUCTS: NONE KNOWN

HAZARDOUS POLYMERIZATION (REACTIVITY): WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EXPOSURE: EYE CONTACT, SKIN CONTACT, INHALATION, INGESTION.

EYES:
ACUTE – MAY CAUSE MILD IRRITATION WITH BLURRED VISION.
CHRONIC – ND

SKIN CONTACT:
ACUTE – TRANSIENT IRRITATION AND REDNESS.
CHRONIC – ND

SKIN ABSORPTION:
ACUTE – ND
CHRONIC – ND

INHALATION:
ACUTE – INHALATION OF MISTS MAY CAUSE MILD RESPIRATORY TRACT IRRITATION.
CHRONIC – EXCESSIVE EXPOSURE MAY RESULT IN REDUCED FETAL WEIGHT, INCREASE IN FETAL DEATHS AND SKELTAL MALFORMATIONS

INGESTION:
ACUTE – MAY CAUSE MILD IRRITATION OF GASTRO-INTESTINAL TRACT
CHRONIC – EXCESSIVE EXPOSURE MAY RESULT IN REDUCED FETAL WEIGHT, INCREASE IN FETAL DEATHS AND SKELTAL MALFORMATIONS

SAFETY DATA SHEET

VAPORSOLVE® TIE COAT PART B

Page 5 of 6

SECTION 11: TOXICOLOGICAL INFORMATION CON'T.

ACUTE TOXICITY: NO DATA ON THE PRODUCT ITSELF

ACUTE ORAL TOXICITY- COMPONENTS

2-PROPOXYETHANOL LD50: 3090 mg/kg SPECIES: RAT

ACUTE DERMAL TOXICITY- COMPONENTS

2-PROPOXYETHANOL LD50: 870 mg/kg SPECIES: RABBIT

ACUTE INHALATION TOXICITY- COMPONENTS

2-PROPOXYETHANOL ND

SKIN CORROSION/IRRITATION
IRRITATION

SERIOUS EYE DAMAGE/EYE IRRITATION
SERIOUS EYE IRRITATION

SENSITIZATION

MAY CAUSE AN ALLERGIC REACTION AFTER A SINGLE EXPOSURE OR WITH REPEATED OR PROLONGED SKIN CONTACT

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (SINGLE EXPOSURE)

CATEGORY 3, RESPIRATORY TRACT. CATEGORY 2, EYES, BLOOD, LIVER

SPECIFIC TARGET ORGAN SYSTEMIC TOXICITY (REPEATED EXPOSURE)

CATEGORY 2 SKIN, KIDNEYS, ADRENAL. CATEGORY 1 LUNGS

GERM CELL MUTAGENICITY:

ANIMAL TESTING ON THIS SUBSTANCE INDICATE POSSIBLE MUTAGEN; TESTS ON BACTERIAL AND MAMMALIAN CELL CULTURES DID NOT SHOW MUTAGENIC EFFECTS.

CARCINOGENIC DATA:

NOT CLASSIFIED AS CARCINOGENIC. NOT LISTED BY OSHA/NTP/IARC

REPRODUCTIVE TOXICITY:

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. AVOID EXPOSURE TO WOMAN DURING EARLY PREGNANCY

SECTION 12: ECOLOGICAL INFORMATION

TOXICITY

AQUATIC TOXICITY: ND

PERSISTENCE AND DEGRADABILITY

BIODEGRADABILITY: ND

BIOACCUMULATIVE POTENTIAL

BIOACCUMULATION: 2-PROPOXYETHANOL- BIOCONCENTRATION POTENTIAL IS LOW

PARTITION COEFFECIENT: N-OCTANOL/WATER(LOG P_{ow}): ND

MOBILITY IN SOIL: ND

