

S-200 Super-Scrub™

TECHNICAL DATA SHEET

DESCRIPTION

S-200 Super-Scrub™ is a non-lotion cleaner used primarily for the removal of S-1710 Liquid Release Agent™ residue from stamped concrete and stampable overlays. S-200 Super-Scrub ensures the removal of release agents residue without creating a film or bond-breaker. It may also be used as a multi-purpose cleaning products for general cleaning of driveways, decks, parking lots, building exteriors, vehicles and hard or soft materials and tools. S-200 Super-Scrub is in concentrated form, rinses clean, is non-corrosive and can be shipped by standard freight.

USES

Concrete / Asphalt Surfaces
Interior / Exterior Use
Automotive Industry
General Cleaning

Cleaner and Degreaser
Commercial Kitchens
Surface Preparation

ADVANTAGES

Environmentally Safe
Leaves No Residue
Lotion-Free

Multi-Purpose
Non-Corrosive
Biodegradable

CSI RELATED SECTIONS

03 01 40.51 - Cleaning of Cast Decks and Underlayment
04 01 20.51 - Unit Masonry Cleaning
04 01 40.51 - Stone Cleaning
09 01 90.51 - Paint Cleaning



MIXING

Super-Scrub can be diluted with clean water up to 2000%. Mix 1 part Super-Scrub with 20 parts clean water.

APPLICATION

Remove all excess dirt and other surface contamination that will prevent penetration and activation of S-200 Super-Scrub. S-200 Super-Scrub can be spray-applied or poured directly onto the surface and immediately spread and worked into the surface with a stiff-bristled broom. When spraying on smaller projects, use a small hand pump type sprayer. Scrub well and allow product to penetrate and clean the surface for a minimum of five minutes followed by rinsing with clean water. Proper use of a water blaster to remove remaining products will yield best results.

Coverage Rate

Spray Application 6000 sf / gallon

**Coverage rates will vary, these are approximations only. Actual coverage will vary due to substrate conditions, surface porosity and method of application.*

Shelf Life 5 years when properly stored.

Storage Store in a cool, dry place.
Keep from moisture and freezing.

Tools Required

Hand-pump sprayer Soft-bristled broom
Water blaster

Appearance Translucent blue liquid

Odor Slight

V.O.C. Content < 100 g/liter

Packaging 1 gallon bottle / 4 per case
5 gallon pail / 36 per pallet

pH 9.5-10.3

Specific Gravity 1.04

Super-Krete® Products is a Division of Arizona Polymer Flooring, Inc.

© 2017 Arizona Polymer Flooring, Inc
4565 W Watkins St. / Phoenix, AZ 85043 / 800.562.4921
623.435.2277 Tel. / 623.435.8585 Fax

www.super-krete.com

S-200 Super-Scrub™ 032317



CAUTION

Keep away from children. Do not take internally. Always use safety gloves, the appropriate eye protection, and appropriate OSHA/NIOSH approved respirator in areas with poor ventilation and when exposed to spray mist, both indoors and outdoors. If ingested, seek medical attention immediately.

LIMITATIONS:

Super-Krete Products are to be applied only when surface temperatures are above 55°F and rising and not to exceed 100°F. Super-Krete Products are not to be applied when precipitation is expected within 24 hours following completion of application. Do not allow materials to freeze. Each Super-Krete product acts as an inherent part of a proven system. Super-Krete Products are professional, contractor grade products. Training in the use of these products is available. Consult a Super-Krete Products representative for information and assistance locating approved contractors in your area or for training class dates.

MOISTURE VAPOR EMISSIONS PRECAUTIONS:

All concrete floors not poured over an effective moisture vapor retarder are subject to possible moisture vapor transmission that may lead to blistering and failure of the coating system. It is the coating applicator's responsibility to conduct calcium chloride testing in compliance with ASTM F1869, or relative humidity probe testing in compliance with ASTM-F2170, to determine if excessive levels of vapor emissions are present before applying any coatings. Arizona Polymer Flooring offers **S-1300 Pene-Krete®** for cementitious overlay products and **VaporSolve® Moisture Remediation** systems for resinous floor coatings. Consult our technical service department. Arizona Polymer Flooring and its sales agents will not be responsible for coating failures due to undetected moisture vapor emissions.

WARRANTY:

Arizona Polymer Flooring guarantees that this product is free from manufacturing defects and complies with our published specifications. In the event that the buyer proves that the goods received do not conform to these specifications or were defectively manufactured, the buyer's remedies shall be limited to either the return of the goods and repayment of the purchase price or replacement of the defective material at the option of the seller. ARIZONA POLYMER FLOORING MAKES NO OTHER WARRANTY, EXPRESSED OR IMPLIED, AND ALL WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE HEREBY DISCLAIMED. Arizona Polymer Flooring shall not be liable for damages caused by application of its products over concrete with excessive moisture vapor transmission or alkalinity. Arizona Polymer Flooring shall not be liable for any injury incurred in a slip and fall accident. Manufacturer or seller shall not be liable for prospective profits or consequential damages resulting from the use of this product.

Super-Krete® Products is a Division of Arizona Polymer Flooring, Inc.

© 2017 Arizona Polymer Flooring, Inc

4565 W Watkins St. / Phoenix, AZ 85043 / 800.562.4921

623.435.2277 Tel. / 623.435.8585 Fax

www.super-krete.com

S-200 Super-Scrub™ 032317

