



DURALIFE® EXTREME PRESSURE RACING GEAR OIL SAE 250

Duralife® Extreme Pressure Racing Gear Oil SAE 250 is formulated with premium quality base stocks and the high zinc, sulfur-phosphorus, anti-wear and extreme pressure additive technology to provide the maximum differential performance and life for conventional rear axles, limited slip rear axles, and transmissions requiring EP gear oils under high speed, heavy load, high torque, and high horsepower conditions.

APPLICATIONS:

Duralife® Extreme Pressure Racing Gear Oil SAE 250 is recommended for use in hypoid or spiral bevel gear of off-road trucks, rock racers, rock crawlers, pulling tractors, funny cars, dragsters, heavy-duty trucks and equipment operating under severe conditions and required a high-viscosity API GL-5 gear oil.

BENEFITS:

- Good oxidation, thermal stability.
- Protects gear teeth against pitting, spalling and scouring.
- Non-corrosive to steel and other metals.
- Excellent anti-wear, antirust, anticorrosion, antifoam properties.

TYPICAL CHARACTERISTICS

Test	Method	Typical results
SAE Grade		250
API Gravity	ASTM D287	25.72
Specific Gravity@ 15.6°C (60°F)	ASTM D1298	0.90
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D445	696.47 42.72
Viscosity Index	ASTM D2270	103
Flash Point, °C (°F)	ASTM D92	320(608)
Pour Point, °C (°F)	ASTM D97	-15(5)
Zinc, ppm	ASTM D 6481	3100
Phosphorus, ppm	ASTM D 6481	2900

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers.

Reference SDS Number 12026 database on our website at www.amtecol.com
OR scan the code for a direct link

