



## ***SUPER LIFE® 9000L*** **FULL SYNTHETIC MOTOR OILS**

*SUPER LIFE® 9000L Products* are manufactured with Synthetic base stocks and the most advanced additive technology to provide ultimate engine protection while meeting the latest requirements for modern engines.

### **APPLICATIONS:**

*SUPER LIFE® 9000L Products* meet the performance requirements of virtually all engines used in passenger cars, light- trucks vans operating in any type of severe service (extreme hot or cold climates, stop- and- go driving conditions, etc.)

API SL/SJ: SAE 5W-20, 5W-30, 10W-30

API SL/SJ/CF: SAE 5W-40, 10W-40

ILSAC GF-3: SAE 5W-20, 5W-30, 10W-30

Energy conserving: SAE 5W-20, 5W-30, 10W-30

*SUPER LIFE 9000L Products* meet the requirements of major North America, Japanese and European OEMs: Ford, General Motors, Mercedes Benz, Volkswagen, Porsche, Peugeot, Fiat, Toyota, Honda, Nissan, etc.

### **BENEFITS:**

- Ultimate engine protection. Increase thermal and oxidation stability at extreme high temperatures.
- Faster cold start and improve oil flow at extreme low temperature.
- Lower oil consumption under high-speed conditions.
- Protect against rust and corrosion caused by severe low temperature stop- and -go driving.
- Protect against harmful deposits and acid.
- Fuel efficiency
- Extend engine life
- Excellent at maintaining engine cleanliness.

### **TYPICAL CHARACTERISTICS**

Test	Method	Typical Results				
		5W-20	5W-30	5W-40	10W-30	10W-40
SAE Viscosity Grade	SAE J300					
API Gravity	ASTM D 287	34.97	34.58	34.19	33.80	33.42
Specific Gravity @ 15.6 °C (60°F)	ASTM D1298	0.850	0.852	0.854	0.856	0.858
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D445	46.93 8.58	60.0 10.88	86.0 13.90	62.5 10.38	97.2 14.20
Viscosity Index	ASTM D2270	162	175	166	155	150

Flash Point, °C (°F)	ASTM D92	230(446)	230(446)	230(446)	230(446)	230(446)
Pour Point, °C (°F)	ASTM D97	-36 (-33)	-40 (-40)	-42 (-44)	-41 (-42)	-40 (-40)

*The above characteristics are average values based on recent production. Minor variations, which do not affect product performance, are to be expected in normal manufacture.*

**WARNING:**

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS Number 12022 database on our website at [www.amtecol.com](http://www.amtecol.com)  
OR scan the code for a direct link

