SUPER LIFE® 6500M-4T SB SCO
SUPREME SYNTHETIC BLEND 4-STROKE SCOOTER OILS

SUPER LIFE® 6500M-4TSB SCO Products are supreme quality lubricants specially designed to ensure ideal protection for the engine, transmission used by all 4-stroke modern Scooters. They are formulated with a unique additive package chosen and a mixture of high-tech synthetic and premium quality base stocks for exceptional wear protection, sludge and varnish resistance, and thermal stability.
High engine RPM and the operating temperatures of Scooter air-cooled or liquid-cooled engines fluctuate greatly, causing conventional lubricants to lose viscosity and reduce their ability to control wear, resulting in power loss and in shorter engine life. Formula 4-stroke synthetic blend Scooter oils with low friction additives help reduce power losses, resist shear and breakdown at elevated temperatures, maintaining their protective viscosity for excellent wear protection, minimizing friction for maximum power and extended engine life. They deliver maximum horsepower.

APPLICATIONS:

SUPER LIFE® 6500M-4TSB SCO Products are recommended for all types of 4-stroke modern Scooters of European, Japanese, Taiwanese, Chinese, Indian manufacturers including VESPA, PIAGGIO, PEUGEOT, HONDA, SUZUKI, YAMAHA, KAWASAKI, APRILIA, BENELLI, SYM, KYMCO, TGB etc.
Meet:
API SM
JASO MB

BENEFITS:

- Help engine reach maximum performance and power, quick starting up .
- Protect well heavy loaded parts in very severe conditions of operating : high speed, high temperature, rough roads .
- Provide maximum anti-wear protection for bearing, val-trains, rings, cylinders and pistons, and lubricity for low friction.
- Provide good characteristics in harmful deposit control to help keep the engine and transmission running cleaner.
- Enhanced shear stability for engine running smoothly and freshly.
- Reduced vibration and engine noise.
- Help reduce foaming and air-entrainment in high speed engines.
- Excellent fuel saving, lengthen the oil changing intervals, economize everything . Prolong engine life .

TYPICAL CHARACTERISTICS

Test	**Method**	**Typical Results**		
SAE Viscosity grade	SAE J300	10W-30	10W-40	20W-50
API Gravity	ASTM D287	31.89	31.33	30.77

Specific gravity @ 15.6ºC (60ºF)	ASTM D1298	0.866	0.869	0.872
Viscosity @ 40ºC cSt @ 100ºC cSt	ASTM D445	72.5 11.5	101.30 15	161 20.45
Viscosity Index	ASTM D2270	153	155	148
Flash Point, ºC (ºF)	ASTM D92	205(401)	205(401)	210(410)
Pour Point, ºC (ºF)	ASTM D97	-37(-35)	-37(-35)	-26(-15)
Total Base Number, mgKOH/g	ASTM D2896	7.5	7.5	7.5

The above characteristics are average values based on recent production.
Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:
Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.
Don't pollute. Conserve resources. Return used oil and bottle to collection centers
Reference SDS Number 12023 database on our website at ***www.amtecol.com*** *OR scan the code for a direct link*