



SUPER LIFE® 5500-2T PREMIUM LOW SMOKE 2-STROKE MOTORCYCLE OIL

SUPER LIFE® 5500-2T is a premium quality two - stroke engine oil specially formulated from highly refined base oils with low ash additive package to provide excellent clean-burning performance while protecting vital system parts.

APPLICATIONS:

SUPER LIFE® 5500-2T is recommended for two - stroke engines having either self-mixing or lube injection lubrication systems and suitable for all two - stroke motorcycle engines of Europe, Japan, USA: VESPA, PIAGGIO, HONDA, SUZUKI, YAMAHA, KAWASAKI, etc. Meet:

API TC + (TSC-3)
JASO FC ISO-L-EGC



BENEFITS:

- Excellent engine protection, maintains strong capacity, prevents deposits on piston, spark-plug and in chimney pot . High reduction of exhaust smoke emissions . Keeps engine always clean .
- Provides exceptional lubricity and protection against piston scuffing ,ring sticking and bearing wear, rust and corrosion.
- Helps engine running smoothly, freshly and strongly spurting out . Excellent fuel saving .
- Good dissolving in fuel with ratios from 50:1 up to 10:1 (2% to 10%) according to the engine manufacturer’s recommendations.

TYPICAL CHARACTERISTICS

Test	Method	Typical results
API Gravity	ASTM D287	31.51
Specific Gravity@ 15.6°C (60°F)	ASTM D1298	0.868
Viscosity @ 40°C, cSt @ 100°C, cSt	ASTM D445	58 8.5
Viscosity Index	ASTM D2270	119
Flash Point, °C (°F)	ASTM D92	110 (230)
Pour Point , °C (°F)	ASTM D97	-15 (5)

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and bottle to collection centers

Reference SDS Number 12025 database on our website at www.amtecol.com

OR scan the code for a direct link

