



SUPER LIFE® 7500 **MOTOR OILS**

SUPER LIFE® 7500 Products are manufactured with the latest additive systems and premium quality base oils to provide extraordinary engine protection under all severe driving conditions, including heavy load and stop- and -go conditions.

They are specifically designed to meet the demands of today's high- performance modern engines.

APPLICATIONS:

SUPER LIFE® 7500 Products are recommended for gasoline engine used in passenger cars, light-duty trucks, vans, including turbocharged engines.

API SL/SJ: SAE 30, 40, 50, 5W-20, 5W-30, 10W-30, 10W-40, 20W-50

IL SAC GF-3: SAE 5W-20, 5W-30, 10W-30

Energy Conserving: SAE 5W-20, 5W-30, 10W-30

BENEFITS:

- Excellent resistance to thermal breakdown at high temperature.
- Flow easily at low temperature for easy cold starting and rapid warm up
- Help protect against start up wear, rust and corrosion
- Good anti-foaming characteristics and shear stability
- Excellent protection from engine sludge and varnish deposits
- Improve fuel economy, oil economy
- Extend engine life
- Excellent at maintaining engine cleanliness

TYPICAL CHARACTERISTICS

Test	Method	Typical results							
		30	40	50	5W-20	5W-30	10W-30	10W-40	20W-50
SAE Viscosity grade	SAE J300	30	40	50	5W-20	5W-30	10W-30	10W-40	20W-50
API Gravity	ASTM D287	27.30	26.60	26.25	33.03	32.08	30.21	29.47	28.38
Specific gravity @ 15.6°C (60°F)	ASTMD1298	0.891	0.895	0.897	0.860	0.865	0.875	0.879	0.885
Viscosity @ 40°C, cst @ 100°C, cst	ASTMD445	87.9 11	136.8 14.5	219.3 20.0	55.7 9.1	65.75 10.93	70.2 10.4	101.2 14	180.5 19.1
Viscosity index	ASTMD2270	111	105	105	145	158	134	140	120
Flash point, °C (°F)	ASTMD92	220 (428)	230 (446)	235 (455)	205 (401)	205 (401)	210 (410)	220 (428)	225 (437)
Pour point, °C (°F)	ASTMD97	-12 (10.4)	-12 (10.4)	-12 (10.4)	-35 (-31)	-36 (-33)	-32 (-26)	-32 (-26)	-26 (-15)

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING:

Continuous contact with used motor oil has caused skin cancer in animal tests. Avoid prolonged contact. Thoroughly wash exposed areas with soap and water. Keep out of reach of children.

Don't pollute. Conserve resources. Return used oil and container to collection centers

Reference SDS Number 12021 database on our website at www.amtecol.com OR scan the code for a direct link

