



DURALIFE® PRE-DILUTED 50/50 EXTENDED LIFE ANTIFREEZE / COOLANT (GREEN COOLANT 50/50)

Duralife® Pre-diluted 50/50 Extended Life Antifreeze / Coolant (Green Coolant 50/50) is an ethylene glycol/water based formulation. It is ready to use without adding water. This product protects all metal surfaces within the cooling system including solder, copper, brass, steel, cast iron, and aluminum. The effectiveness of the coolant is improved by the anti-foam properties which works by preventing air bubbles from forming and interfering with the coolants ability to cool.

APPLICATIONS:

Duralife® Pre-diluted 50/50 Extended Life Antifreeze / Coolant (Green Coolant 50/50) is recommended for automotive and truck cooling systems and other industrial machines.

Duralife® Pre-diluted 50/50 Extended Life Antifreeze / Coolant (Green Coolant 50/50) provides protection over a temperature range from -37°C (-34°F) to 129°C (265°F).

It meets the following specifications:

- ❖ ASTM D3306, D 6210, D 6211, D7583, D7820.
- ❖ SAE J1034, J1941, J814C, J1038
- ❖ GM 6043M/1825M /1899M , TMC RP-329 /RP-338, MIL CID A-A 52624-I-IP-II, Caterpillar EC-1, JASO M325, JIS K 2234 (Japan Standard), DDC7SE 298, PACCAR, MAN 324, Freightliner 48-22880, John Deere JDM H24, Kenworth R 026167097, MTU MTL 5048, Mack 01GS17004/014GS17009, Peterbilt, International, Volvo.
- ❖ Mercedes, BMW, Audi, Toyota/Lexus, Nissan/Infiniti, Subaru.

BENEFITS:

- This product will provide up to 12,000 hours or 600,000 miles in-field service life.
- Provides excellent protection for both automotive and heavy duty diesel engines.
- Constant cooling through improved heat exchange in the cooling system.
- Prevents foaming and provides protection against rust and corrosion.
- No effects on automotive rubber hoses, gaskets and synthetic parts.
- Low silicate formulation that reduces drop-out and silicate gel formation.
- Improved hard water stability, due to the absence of phosphates.
- Compatibility with most major brands of coolant.
- Storage stable for at least 8 years.

TYPICAL CHARACTERISTICS

Test	Method	Typical results
Color		Red
PH	ASTM D1287	7.5 – 10.0
Specific Gravity @ 15.6°C (60°F)	ASTM D1298	1.06 – 1.10
Freezing point, °C(°F) max	ASTM D1177	-37 (-34)
Boiling point ,°C(°F) min	ASTM D1120	108 (226)
Water, %wt	ASTM D 1123	50

The above characteristics are average values based on recent production. Minor variations which do not affect product performance are to be expected in normal manufacture.

WARNING: Corrosion liquid! Harmful if takes internally. Keep out of reach of children and avoid contact with eyes. Do not discharge used liquid into drains.

Reference SDS Number 12028 database on our website at www.amtecol.com OR scan the code for a direct link.

